GL00036

FC USGS OFR 79-942

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Uranium and organic matter: Use of pyrolysis-gas chromatography, carbon, hydrogen and uranium contents to characterize the organic matter from sandstone-type deposits

By

Joel S. Leventhal

UNIVERSITY OF UTAM RESEARCH INSTITUTE EARTH SCIENCE LAD.

Open File Report 79- 942

This report is preliminary and has not been edited or reviewed for conformity with U.S. Geological Survey standards,

Table of Contents

Page

Abstract	1
Introduction	2
Experimental	3
Results	4
Discussion	8
References	9

Illustration

Figure 1. Typical programs from stepwise pyrolysis gas chromatography of organic materials associated with sandstone-type uranium ores......5

Table

Table 1. Pyrolysis type, uranium content, and H/C (atomic) ratio for organic matter associated with uranium sandstone ores......7

Uranium and organic matter: Use of pyrolysis-gas chromatography, carbon, hydrogen and uranium contents to characterize the organic matter from sandstone-type deposits

By

Joel S. Leventhal

Abstract

Organic matter seems to play an important role in the genesis of uranium deposits in sandstones in the western United States. Organic materials associated with ore from the Texas coastal plain, Tertiary basins of Wyoming, Grants mineral belt of New Mexico, and the Uravan mineral belt of Utah and Colorado vary widely in physical appearance and chemical composition.

Partial characterization of organic materials is achieved by chemical analyses to determine atomic hydrogen-to-carbon (H/C) ratios and by gas chromatographic analyses to determine the molecular fragments evolved during stepwise pyrolysis.

From the pyrolysis experiments the organic materials can be classified and grouped: (a) lignites from Texas and Wyoming and (b) hydrogen poor materials, from Grants and Uravan mineral belts and Wyoming; (c) naphthalenecontaining materials from Grants mineral belt and Wyoming; and (d) complex and aromatic materials from Uravan, Grants and Wyoming.

The organic materials analyzed have atomic H/C ratios that range from approximately 0.3 to at least 1.5. The samples with higher H/C ratios yield pyrolysis products that contain as many as 30 carbon atoms per molecule. Samples with low H/C ratios are commonly more uraniferous and yield mostly methane and low-molecular-weight gases during pyrolysis.

Introduction

Sandstone-type uranium deposits, which make up more than 90 percent of the U.S. production and reserves, usually have organic material intimately intermixed in the ore. The major uranium districts are in the Wyoming basins (for example, Harshman, 1972), the Texas coastal plain (for example, Eargle and others, 1975), the Grants mineral belt in New Mexico (for example, Granger and others, 1961), and various localities in the Uravan mineral belt of eastern Utah and southwestern Colorado (for example, Shawe and others, 1959).

The Wyoming and Texas deposits are of the "roll" type, where the ore is between oxidizing updip and reducing downdip zones in sandstone beds that are sandwiched between lower permeability clays. The genesis of these ores has been discussed (Harshman, 1974) and related to a biogenic model (Rackley, 1972) and a nonbiogenic model (Granger and Warren, 1969), both involving reduction of uranium at the roll interface. Organic material is observed in these deposits as coalified or mineralized logs, millimeter-size coaly material, and amorphous organic material. The deposits are commonly in close proximity to seams of lignite. The lignite is not mineralized but could be a source of humic materials.

The New Mexico and Colorado-Utah deposits are mainly of the "tabular" type, where the ore is "floating" in sandstone bodies. The ore is generally associated with coalified wood (Breger, 1974) or with insoluble, unstructured organic material, which may have originially been of a humic acid type (Granger and others, 1961; Jacobs and others, 1970). The genesis of these ores is related to fixation of uranium by organic matter, perhaps through precipitation at an interface of two dissimilar water bodies (Granger and others, 1961; Shawe and others, 1959).

Experimental Procedure

Stepwise pyrolysis-gas chromatography has been described by Leventhal (1975, 1976), and the experimental procedure is only briefly reviewed here. First, 1 to 10 mg of finely powdered sample is placed in a 2.5-cm by 2-mm (ID) quartz tube, which is then put in the spiral heating coil of the Pyroprobe (Chemical Data Systems, Oxford, Penn.)*. The Pyroprobe is inserted in the injection port of a gas chromatograph in helium carrier gas ($12 \text{ cm}^3/\text{min}$) and pyrolyzed for 10 seconds at 250°C. The pyrolysis products then pass into a 15-m by 0.05-mm (ID) porous-layer-open-tabular (PLOT) capillary column coated with Apiezon L on Chromsorb R-6740 and are trapped within the first 6 cm of column, which has been immersed in liquid nitrogen. The pyrolysis products are temperature programed at 6°/min from 50° to 280°C after the trap has warmed to room temperature (from liquid N₂ temperature). The procedure is repeated at 450°, 600°, 750°, and 900°C (and sometimes 1050° and 1200°C), and sometimes pyrolysis products from several steps are combined.

Elemental analyses were done using a Perkin Elmer^{**}C, H, and N analyzer after carbonates had been removed by acid leaching. Carbon was analyzed as follows: Total was by Leco^{**} combustion, carbonate by acid-leach gasometry, and organic by difference (Leventhal and others, 1978).

Uranium was analyzed by the delayed neutron technique (Millard, 1976) at the U.S. Geological Survey analytical laboratories in Denver.

*Use of brand names herein is for identification only and does not imply endorsement by the U.S. Geological Survey.

Results

Pyrolysis-gas chromatography is used to characterize insoluble organic matter. Pyrolysis can fragment the large insoluble organic molecules into smaller pieces that can be identified. The stepwise pyrolysis procedure enables the removal of volatile or soluble molecules at low temperature without the usual chemical solvent extraction. These volatile or soluble species may be of recent origin and may not be related to the organic matter that "fixed" the uranium.

The organic matter associated with sandstone-type uranium deposits can be classified into four types by pyrolysis-gas chromatography (Leventhal 1975, 1976). Figure 1 shows typical pyrograms obtained from study of more than 100 samples from western U.S. sandstone deposits.

The pyrograms represent molecules with 9 to 30 carbon atoms. The large peaks of pyrogram (a) represent the normal (or linear straight-chain) alkanes and alkenes. Alkenes are molecules with an unsaturated carbon (carbon-carbon double bond). The numbers show the number of carbon atoms in the molecule (e.g. $n-C_{12}$ is $C_{12}H_{26}$ (alkane) and $C_{12}H_{24}$ (alkene)). The samples that give pyrogram (a) are lignites (or low-grade coaly material) from beds that underlie or overlie uranium deposits in Wyoming and Texas. These pyrograms look the same as pyrograms of nonmineralized lignites from other localities.

Pyrogram (b) shows no molecules with nine or more carbons. (The "hump" represents small amounts of unresolved molecules or column bleed.) The samples that give this type of pyrogram may have carbon content as high as several percent, but the only pyrolysis products are methane and other gases (not shown on fig. 1). These gases are not part of the organic matter but are synthesized by the high pyrolysis temperature through the reaction of hydrogen from water the clays present in the samples. These samples are ores from the

Figure 1. Stepwise pyrolysis gas chromatography of organic materials associated with sandstone - type uranium ores. Detector response is shown on the abscissa and column temperature on the ordinate. See text for discussion.



Grants mineral belt and Uravan mineral belt and are amorphous-structureless organic matter intimately mixed with uranium (Granger and others, 1961). The H and C analyses (see table 1) show that they are hydrogen deficient, in some cases approaching amorphous carbon.

Pyrogram (c) shows only one large peak and several very small peaks. The large peak has been identified by mass spectrometry as having a mass/energy ratio of 128, which is characteristic of naphthalene ($C_{12}H_{10}$, two fused aromatic rings). Naphthalene is a molecule that should be stable to oxidation, temperature, and radiation. The small peaks present are below the sensitivity of the mass spectrometer and cannot be identified. The organic materials in these samples are similar to type (b): they are structureless and hydrogen poor.

Pyrogram (d) is a complex mixture, which has been partly characterized by mass spectrometry. The identified peaks are a benzene nucleus with functional groups such as hydroxyl (OH), methoxyl (OCH₃), and methyl (CH₃). These are representative of the structures of lignin (Sigleo, 1978). The samples that give pyrogram (d) are from ores that are associated with structured material that looks like coalified logs and fossil wood fragments.

Discussion

Stepwise pyrolysis gas chromatography is a useful technique which allows analysis of insoluble sedimentary organic material. Four types of organic matter have been found from western U.S.-sandstone type uranium deposits. The material represented by pyrogram (b) is the most altered, and its origin is not elucidated by pyrolysis-gas chromatography. It is possible that type (b) has evolved from type (c), and both of these could have come from either type (a) or (d). The pyrograms show the chemical building blocks of mineralized and nonmineralized lignite type (a) and mineralized coaly material type (d). Unfortunately, the amorphous material of the Grants mineral belt has not given pyrolysis products that can be related to an organic precursor.

Sanastone ores			
iample	ppm U	% C org	H/C*
Type (a) Alkanes and alken	es		
8.3 lignite, Wyoming ignite, Powder River Basin, Highland Mine, Wyoming eiker Mine, lignite, Texas	352 3 1,000 133	2.0	16.6
owder River Basin 472 ft, fossil vegetal matter, wyoming owder River Basin 447 ft, Wyoming coal, New Mexico stoeltje Mine, lignite 12, Texas stoeltje Mine, upper lignite, Texas searcy Mine, middle lignite, Texas	5,450 544 0.9 	19.1 0.72 51.4 20.1 48.9 13.2	0.61 1.12 1.10 1.36
Type (b) H-poor			
972975 Uravan, amorphous, Utah. 072375 Uravan, amorphous, Utah. Jackpile, amorphous, New Mexico. 5.5 Paguate, amorphous, New Mexico. 6661 i, Ambrosia Lake, New Mexico. 6662 i, Ambrosia Lake, New Mexico. 6663 i, Ambrosia Lake, New Mexico. 6663 i, Ambrosia Lake, New Mexico. 6664 i, Ambrosia Lake, New Mexico. 6655 i, Ambrosia Lake, New Mexico. 6665 i, Ambrosia Lake, New Mexico. 6667 i, Ambrosia Lake, New Mexico. 6670 i, Ambrosia Lake, New Mexico. 6670 i, Ambrosia Lake, New Mexico. 6700 i, Ambrosia Lake, New Mexico. 6	15,640 5,987 4,450 11,000 15,000 5,077 363 10,800 27,700 10,860 5,930	1.7 0.7 1.8 3.7 0.7 0.1 9.1 1.1 5.0 45.1 26.5	0.62
Type (c) Naphthalene			
<pre>I5G62 Poison Canyon, Ambrosia Lake, New Mexico 2-6-8-75 Salt Wash, Coaly, Utah J 16 Stoeltje, lignite, Texas 16.1 Pawelek (black), lignite, Texas 16.2 Pawelek (red), Texas 16G58 Wood? Bone? Asphalt?, New Mexico 37G62, Coal N58, New Mexico 1960 Kermac Sec 30, fracture filling, New Mexico</pre>	3,145 39,462 1,414 1,586 866	62 33 28 26 2.5 39.8 55.6 39	0.39 0.88 (1.67) 0.49 0.46
Type (d) Complex and aroma	tic		
14G58amorphous, New Mexico.1572975coaly, Uravan, Utah.1672975coaly, Uravan, Utah.cottonwood Wash Mine, coaly, Uravan, Utah.cottonwood Wash Mine, coaly, Uravan, Utah.(12Shirley Basin, Wyoming.(L4Shirley Basin, Wyoming.(YSBA2Shirley Basin, coaly, Wyoming.3lack Diamond Mine, New Mexico.Highland Mine, Powder River Basin, Wyoming.	20,000 8,960 9,030 125 5,483 806 11,460 210 692	30 73 61 70 2.8 13 42 2.6 57	(1.51) 0.85
III-/ IIgnite, Rajah, Utah	65 51 44 130,000 180 80 155 	35.2 2.3 34.2 32.2 2.6 40.8 31.1 4.4 57.5 57.1 9.4	0.83 0.67 0.68 0.69 3.4 0.67 0.77 0.75 0.69 0.70 0.92
lighland Mine, #3 Wyoming Jtah Int, Shirley Basin, Wyoming Log, Uravan, Utah 17-7-29-75, Utah 19.2 Gas Hills, Wyoming	125 105 3,700	46.9 63.9 70.4 69.7 60.9	0.72 0.74 0.89 0.71 0.67

Table 1.--Pyrolysis type, uranium content, carbon content, and H/C (atomic) ratio for organic matter associated with uranium sandstone ores

*All H/C data may include inorganic H from water (in clays, etc); numbers greater than 1 given in parentheses are not considered reliable for this organic material.

References

Breger, I. A., 1974, The role of organic matter in the accumulation of uranium: Coal uranium associations. Proceedings Internation Conference on Formation of Uranium Ore Deposits: International Atomic Energy Agency, Vienna, p. 99-123.

Eargle D. H., Dickinson K. A., and Davis B. O., 1975, South Texas uranium deposits: American Association of Petroleum Geologists Bulletin, v. 50, p. 766-779.

Harshman E. N., 1972, Geology and uranium deposits, Shirley Basin Area, Wyoming: U.S. Geological Survey Professional Paper 745, 82 p.

Granger, H. C. Santos E. S., Dean , B. G., Moore, F. B., 1961, Sandstone-type uranium deposits at Ambrosia Lake, New Mexico; an interim report: Economic Geology, v. 56, p. 1179-1210.

Granger, H. C., and Warren, C. G., 1969, Unstable sulfur compounds and the origin of roll-type uranium deposits: Economic Geology, v. 64, p. 160-171.

Jacobs, M. L., Warren, C. G., and Granger, H. C., 1970, Chemical extraction of an organic material from a uranium ore: U.S. Geological Survey Professional Paper 700-B, p. B184-186.

Leventhal, J. S., 1975, Characterization of the insoluble organic matter associated with uranium ores [abs.], <u>in</u> Craig, L. C., Brooks, R. A., and Patton, P. C., eds., Abstracts of the 1975 Uranium and Thorium Research and Resource Conference: U.S. Geological Survey Open-File Report 75-595, p. 25.

Leventhal, J. S., 1976, Stepwise pyrolysis-gas chromatography of kerogen in sedimentary rocks: Chemical Geology, v. 18, p. 5-20.

Leventhal and others, 1978, Analytical results for SDO-1 from U.S. Geological

Survey, Denver: U.S. Geological Survey Open-File Report 78-447, 11 p. Millard, H. T., Jr., 1976, Determination of uranium and thorium in USGS

- standard rocks by the delayed neutron technique: U.S. Geological Survey Professional Paper 840, F. J. Flanagan, ed. p. 61-66.
- Rackley, R. I., 1972, Environment of Wyoming Tertiary uranium deposits:

American Association of Petroleum Geologists Bulletin, v. 56, p. 755-774.

Shawe, D. R., Archbold, N. L., and Simmons, G. C., 1959, Geology and uraniumvanadium deposits of the Slick Rock district, San Miguel and Dolores Co, Colorado. Economic Geology, v. 54, p. 395-415.

Sigleo, A. C., 1978, Degraded lignin compounds identified in silicified wood, 200 million years old: Science, v. 200, p. 1054-1055.