Dresser Atlas

Compensated Densilog / Compensated Neutron / Gamma Ray

API NO. —

File No. —

2" = 100'

COMPANY GETTY OIL COMPANY

WELL COLLINS 79-17

FIELD WILDCAT

COUNTY HUMBOLDT STATE NEVADA

Other Services: DIL, CBL, VDL

Permanent Datum: GL Elevation 4610 Ft. Above Perm. Datum

Log Measured From: KB 26 Ft. Above Permanent Datum

Drilling Measured From: KB

Date	11-14-81	
Run No.	ONE	
Depth-Driller	3935	
Depth-Logger	3933	
Bottom Logged Interval	3926	
Top Logged Interval	2800	
Type Fluid in Hole	GEL CHEM	
Salinity, PPM Cl	1000	
Density	9.2	
Viscosity	40	
Fluid Loss	8.4	
Source of Sample	FLOWLINE	
Rm @ Meas. Temp.	.61 @ 70°F	@ °F
Rmf @ Meas. Temp.	.52 @ 70°F	@ °F
Rmc @ Meas. Temp.	.91 @ 70°F	@ °F
Source: Rmf / Rmc	MEAS / CALC	
Rm @ BHT	.27 @ 130°F	@ °F
Circulation Stopped	1400	
Logging Started	1700	
Logging Completed	2100	
Max. Rec. Temp.	130°F	°F
Equipment Location	13 MILES S. OF LOVELOCK, NEVADA	
Recorded By	D. LEWIS	
Witnessed By	MR. CLAYTON	

FOLD HERE

Remarks:

EQUIPMENT DATA

	RUN NO. 1			RUN NO. 2			RUN NO. 3		
	DIL	CNL-G	GR	DIL	CNL-G	GR	DIL	CNL-G	GR
Tool Series No.	2202	2613	1305	2202	3133	1305			
Serial No.	20209	13281	31126	20209	21897	31126			
Diameter	4x3"	3x13"	3x13"	4x3"	3x13"	3x13"			
Stand-Off Plate		INDURT			INDURT				
Tool Position	12:00-1:00	2600	Pad	12:00-1:00	2600	Pad			
Type	2DCB	2DCB	2DCB	2DCB	2DCB	2DCB			
Source Assbly No.	31320	31320		31320	31320				
Serial No.	200	31589		200	31571				
Detal Series No.	3132	2626	3132	3132	3132	3132			
Serial No.	32028	32028	32028	32028	32028	32028			

LOGGING DATA

Gamma Ray					Compensated Density						Gamma Ray		
Run No.	Depths From	Depths To	Speed Ft./Min.	T.C. Sec.	Density Scale	R_{wa}	R_t	Porosity Scale	Correction Scale	T.C. Sec.	Sens. Settings	Zero Pos. L.H.	API Units/Div.
2002	1899.5'	93'	30	0.01	2x2x5	2.71	1.0	2.13/2.65	.25/.50	0.01	370	0	50
2300	2000.5'	1899.5'	30										
2300	3933.5'	2000.5'	30	0.01	2x2x5	2.71	1.0	2.13/2.65	.25/.50	0.01	370	0	50
2001	2.23"	1899.5'	30										

Gamma Ray					Compensated Neutron					Caliper
Run No.	Depths From	Depths To	Speed Ft./Min.	T.C. Sec.	Sens. LS	SS	Lithology Scale	Porosity Scale		Hole Size Scale
2002	1899.5'	93'	30	0.01	132	105	LIMESTONE	1.0/-.15	-.15/-.25	6"/16"
2300	2000.5'	1899.5'	30	0.01	131	133	LIMESTONE	1.0/-.15	-.15/-.25	6"/16"

Company GETTY OIL COMPANY

Well COLLINS 79-17

Field WILDCAT

County HUMBOLDT

State NEVADA

Drillers T.D. 3935'

Log F.R. 3933'

Log T.D. 3933'

Elevations:

K.B. 3636' D.F. --- G.L. 3610'

REPEAT SECTION