

NEVADA
LANDER
CHEVRON RESOURCES D-RD-79

27-31n-47e MD
HORSE HAVEN AREA
(Temp Gradient well)
U

Contr: Boyles Bros/GTS. Spud 12-6-79, 7 @ 261, drld to 332,
rel Bros rig, MI GTS rig, drld to 2478, 2 3/8 tbg @ 2478, rr
1-18-80, TD 2478 (Tertiary). ...Temperature gradient well, comp 1-18-80.

NV1-022980

 **Petroleum Information.**
CORPORATION
A subsidiary of I.C. Taylor Company

© COPYRIGHTED 1979
REPRODUCTION PROHIBITED Form No. 611

292258

NEVADA
LANDER
CHEVRON RESOURCES D-RD-79

27-31n-47e MD
HORSE HAVEN AREA
(Temp Gradient well)
U

Contr: Boyles Bros/GTS. Spud 12-6-79, 7 @ 261, drld to 332,
rel Bros rig, MI GTS rig, drld to 2478, 2 3/8 tbg @ 2478, rr
1-18-80, TD 2478 (Tertiary). ...Temperature gradient well, comp 1-18-80.

NV1-022980

 **Petroleum Information.**
CORPORATION
A subsidiary of E. I. du Pont de Nemours & Company

© COPYRIGHTED 1979
REPRODUCTION PROHIBITED Form No. 611

Petroleum Information's Well Log Service has available for purchase electrical well logs on more than 80 geothermal wells in nine states. Logs on wells in California may be purchased from West Coast Well Log Service, Box 9279, 4300 Easton Drive, Bakersfield, California 93389. Phone is (805) 327-5393. Logs for all other wells may be ordered from Rocky Mountain Well Log Service, 333 W. Colfax Avenue, Suite 10, Denver, Colorado 80202, phone (303) 893-2771; or from Electrical Log Services, 500 N. Baird Street, Midland, Texas 79701, phone (915) 682-0591. Reference numbers listed should be used when ordering all logs. The log list will be published periodically and expanded as new geothermal logs become available.

LANDERS COUNTY

Chevron Oil Company
 #21-19 Rossi
 Field: Beowawe
 Sec: 19-31N-48E

K2638X	s-2-11-11	1998-5678
K2638Y	s-c-neu-for-den	1998-5680
K2638Z	s-bhc-son	1998-5682
K2639S	s-con-dip	2000-5680
K2639W	s-con-dip	2000-5675
K2639X	s-dip	100-1998
K2639Y	wx-c-asc-vel	94-1996
K2639Z	wx-dip	100-1998
K2640S	ags-temp	0-5530
K2640W	wx-ie	200-1998

LANDERS COUNTY

Chevron Oil Company
 #1-13 Chevron-ATR-Ginn
 Field: Whirlwind Valley Area
 Sec: 13-31N-47E

K2636W	s-ies	126-8
K2636X	s-2-11-11	810-849
K2636Y	s-c-for-den-gr	840-849
K2636Z	s-c-neu	810-850
K2637S	s-directional-log	840-849
K2637W	s-collar-depth	8000-954
K2637X	s-con-dip	840-849
K2637Y	s-con-dip	840-849
K2637Z	s-con-dip	840-849
HC1350A	expl-hc	0-955
K2638S	ags-temp	0-955
K2638W	expl-drilling-rate	0-950