

GL02701-2

Evals x 4716

#7

Schlumberger

BOREHOLE COMPENSATED SONIC LOG (WITH CALIPER)

COUNTY	FIELD or LOCATION	WELL	COMPANY	COMPANY <u>STANDARD OIL COMPANY</u>			
				<u>OF CALIFORNIA</u>			
				WELL <u>HIGHLAND L&L #1 - REDRILL</u>			
				FIELD <u>WILD CAT NW CALDWELL AREA</u>			
				COUNTY <u>PAYETTE</u> STATE <u>IDAHO</u>			
				LOCATION <u>2210' FWL ± 1650' ENL</u>		Other Services:	
				Sec. <u>24</u> Twp. <u>6N</u> Rge. <u>5W</u>			
Permanent Datum: <u>GL</u> , Elev. <u>2631</u>				Elev.: <u>K.B. 2647</u>			
Log Measured From <u>KB</u> , <u>16</u> Ft. Above Perm. Datum				D.F. <u> </u>			
Drilling Measured From <u>KB</u>				G.I. <u>2631</u>			
Date	<u>6-5-73</u>						
Run No.	<u>ONE</u>						
Depth—Driller	<u>11,935</u>						
Depth—Logger	<u>11,950</u>						
Bot. Log Interval	<u>11,947</u>						
Top Log Interval	<u>10,396</u>						
Casing—Driller	<u>13 3/8 @ 3028</u>			@	@	@	@
Casing—Logger	<u> </u>						
Bit Size	<u>9 7/8</u>						
Type Fluid in Hole	<u>GEL-LIGNITE</u>						
Dens.	Visc.	<u>80</u>	<u>57</u>				
pH	Fluid Loss	<u>10.8</u>	<u>8.0 ml</u>		ml		ml
Source of Sample	<u>FLOWLINE</u>						
R _m @ Meas. Temp.	<u>1.24 @ 78 °F</u>	@	°F	@	°F	@	°F
R _m @ Meas. Temp.	<u>1.05 @ 78 °F</u>	@	°F	@	°F	@	°F
R _m @ Meas. Temp.	<u>1.64 @ 78 °F</u>	@	°F	@	°F	@	°F
Source: R _{mt}	R _{mc}	<u>M</u>	<u>M</u>				
R _m @ BHT	<u>0.34 @ 290 °F</u>	@	°F	@	°F	@	°F
Time Since Circ.	<u>8 1/2 HRS.</u>						
Max. Rec. Temp.	<u>290 °F</u>						
Equip.	Location	<u>7503 SAC</u>					
Recorded By	<u>FRID</u>						
Witnessed By	<u>GILBERT</u>						

CONFIDENTIAL

THIS ARTICLE ENTRUSTED TO

FOR ITS SOLE USE AND BENEFIT

