

Petroleum Information's Well Log Service has available for purchase electrical well logs on more than 80 geothermal wells in nine states. Logs on wells in California may be purchased from West Coast Well Log Service, Box 9279, 4300 Easton Drive, Bakersfield, California 93389. Phone is (805) 327-5393. Logs for all other wells may be ordered from Rocky Mountain Well Log Service, 333 W. Colfax Avenue, Suite 10, Denver, Colorado 80202, phone (303) 893-2771; or from Electrical Log Services, 500 N. Baird Street, Midland, Texas 79701, phone (915) 682-0591. Reference numbers listed should be used when ordering all logs. The log list will be published periodically and expanded as new geothermal logs become available.

LOUISIANAVERMILION PARISH

Gruy Federal/DOE  
#2 Beulah Simon  
Field: Cossinade  
Sec: 26-11S-2E  
B3716C s-cbl-cn1-vdl-gr 11550-15204

LOUISIANA  
TERREBONE  
GRUY & ASSOC  
2047 fnl 3100 fwl.

N-1 Tenneco-Fee  
API 17-109-22069

38-19s-19e  
WILDCAT GWX

17,110 test.

OWWO: Formerly Tenneco Oil N-1 Tenneco-Fee. Spud 9/15/78. 13 3/8 @ 4709, 9 5/8 @ 12,586, 7 @ 12,328-13,438, 4 1/2 @ 13,151-17,246. Log Tops: Globorotalia Fohsi Fohsi 13,670, Textularia W 13,830, Globorotalia Fohsi Fohsi 16,620. OTD 17,267. Comp 1/22/79. Temp Abnd. New Info: Re-entered 1/10/80. El: 1. Tieback csg 7 @ surf-13,438, 5 @ 13,148-17,246. Squeezed off with cement. CO liner to 17,242. Ran cement bondlog. Ran pressure test. Comp 4/23/80. J&A.

LA1-062780

 **Petroleum Information.**  
CORPORATION  
a Subsidiary of A.C. Nielsen Company

© COPYRIGHTED 1979  
REPRODUCTION PROHIBITED Form No. 611

LOUISIANA  
ST MARY'S PARISH  
GRUY FEDERAL

2 Fairfax-Foster-Sutter  
API 17-101-21109

6-14s-10e  
Roosevelt Refuge Geo  
thermal Prospect Area.  
PWR E (oil and gas)

---

16,340 ft test; 24 KB. Fr USC&GS Sta  
"Oaklawn" 1931, go S 05 deg 45 min 32 sec W 20,455 to loc;  
OWWO: Formerly Newhoff O&G. Spud 1/10/79. 10 3/4 @ 2987;  
7 5/8 @ 14,375. Ran logs. OTD 16,348.  
New Info: Ran 5 1/2 lnr 11,140-16,340. Perf L Miocene 15,780-15,932 w/4 pf. Oprs  
temp suspended. Drop from report until activity resumes.

LA1-032880



**Petroleum Information.**

CORPORATION

A Subsidiary of A. I. Refining Company

© COPYRIGHTED 1979  
REPRODUCTION PROHIBITED Form No. 611

LOUISIANA  
VERMILION  
GRUY FEDERAL  
se sw 330 fsl 2600 fwl of  
sec 26.

26-11s-2e  
COSSINADE GWX

1 Beulah Simon  
API 17-113-20878

15,231 test.  
(Well number chgd from 2). OWWO. Old Info: Formerly Southport Expl 2  
Beulah Simon. 13 3/8 @ 3500, 7 5/8 @ 13,900. OTD 15,231. Comp. D&A.  
New Info: Re-entered & cleaned out, set 5 1/2 lnr. El: 21 Gr. Perf 14,664-770  
(plover Camarina sd). F/10,963 bbls hot swtr t247,000 CFGPD, 18/64 ck,  
SITP 6323; FTP 5312. OTD 15,231. F 1116 BSWPD, TP 3353, CP 5018, temp  
264°F; F 1076 BSWPD, 245 MCFGPD, STP 3221, CP 4658. F 1100 BWPD, 220  
MCFGPD, 18/64-22/64, FTP 5000, CP 5769. Comp 2/5/80. D&A.

LA1-053080

 **Petroleum Information.**  
CORPORATION  
a Subsidiary of E. I. du Pont de Nemours & Co.

© COPYRIGHTED 1979  
REPRODUCTION PROHIBITED Form No. 611

LAFAYETTE  
EATON OPERATING  
NW ne.

1 P. R. Girouard  
API 17-055-20176

10-11s-5e  
CADE PW

16,500. El: 29 Gr.  
OWWO. Old Info: Formerly Wainoco O&G 1 J Therence Girouard. OTD 15,700.  
13 3/8 @ 3990, 9 5/8 @ 12,640. Comp 5-27-80. D&A.  
New Info: Re-entered 5/27/80. 7 5/8 @ 14,870 w/1150. 15,700 TD. Perf  
Aligocene 14,744-14,819. F 222 MCFGPD, 6000 BWPD, 24/64 ck. FTP 5275.  
SITP 6700. BHSIP 13,141. Comp 7/15/80. D&A.

LA1-092680



© COPYRIGHTED 1979  
REPRODUCTION PROHIBITED Form No. 611

LOUISIANA  
CALCASIEU  
EATON INDUSTRIES  
sw sw ne 2300 fnl 2200  
Tel of sec 21.

1 Prairie Canal  
API 17-019-20938

21-11s-8w  
LAKE CHARLES  
SOUTH PW

Old Well Info: Orig drld for oil & gas by Houston Oil & Minerals Spud  
6-25-80, 13 3/8 @ 3512, 7 5/8 @ 14,171, OTD 15,684 (U/Frio), D&A 10-10-80.  
New Info: Res 10-29-80, CO, ran logs, 5 1/2 @ 15,684, ran CI, perfd & tstd  
14,978-15,005 (U/Fri@), no details, had hole problems, PB to unrptd depth,  
perfd 14,782-14,822, PT of perfs 14,782-14,822: FARO 5000 BWPD (methane  
content 47 scf/bbl; chloride content: 42,600 ppm), FARO 7000 BWPD  
(methane content 43 scf/bbl; chloride content 42,600 ppm), BHP dropped from  
13,000 psi to 7000 psi, TD 15,684 (U/Frio). ...P & A 3-25-81 (re-entered for  
geothermal-pressure research only).



Petroleum Information.  
CORPORATION

1 Subsidiary of P.I. Service Company

LA1-092581

© COPYRIGHTED 1979  
REPRODUCTION PROHIBITED Form No. 611