

CL03108-65-4-102



FILE NO. 2" = 100'

COMPANY: C.E.R. CORPORATION/ERDA  
 WELL: COSO SPRINGS #1  
 FIELD: COSO SPRINGS  
 COUNTY: INYO  
 STATE: CALIFORNIA  
 LOCATION: N/A

Prepared by: DL  
 Log Measured from: KB  
 Drilling Measured from: DL  
 Date: 10-26-77  
 Run No.: 4022  
 Depth-Driller: 4022  
 Depth-Logger: 4017  
 Bottom Logged Interval: 9.5/8 @ 368  
 Casing-Driller: 8 3/4  
 Casing-Logger: 8 3/4

SEC: 6 TWP: 22 S. RGE: 39 E. S. 35  
 T. 35 S. R. 39 E. S. 35  
 0 ft Above Permanent Datum  
 Elevation: 4358.5  
 Elevation: 4358.5

Other Services:  
 TEM: N/A  
 FRAC: N/A  
 Panel No: 32700

REMARKS: (1) BHT DIFFERS FROM TEMPERATURE PROBE MEASUREMENT, (200 VS. 279)  
 (2) LOG DEPTH RESET TO DRILLER DEPTH & NOT CORRECTED FOR MEASUREMENT ERROR WHILE LOGGING.  
 (3) NO REPEAT AT CUSTOMER'S REQUEST


Equipment Used:  
 Series No: 815  
 Run No: 81706  
 Tool No: 38166  
 Elec No: 38166  
 Panel No: 32700

Changes in Mud Type or Additional Samples:  
 Date: Sample No. Type Log Depth Scale Changes Scale Down Hole

Type Fluid in Hole:  
 Dens: Visc: CC: CC:  
 pH: Fluid Loss:  
 Source of Sample:  
 Rm @ Meas. Temp. \*F \*F  
 Rmf @ Meas. Temp. \*F \*F  
 Rmc @ Meas. Temp. \*F \*F  
 Source - Rmf, Rmc:  
 Rm @ BHT \*F \*F  
 Rmf @ BHT \*F \*F  
 Rmc @ BHT \*F \*F

Equipment Data:  
 Run No: 815  
 Tool Type: ONE  
 Pad Type: -  
 Tool Position: S.O.

| SPONTANEOUS POTENTIAL<br>Millivolts | DEPTH     | RESISTIVITY<br>Ohms m <sup>2</sup> /m | CONDUCTIVITY<br>Millimhos/m           |
|-------------------------------------|-----------|---------------------------------------|---------------------------------------|
|                                     |           | INDUCTION RESISTIVITY<br>40" SPACING  | INDUCTION CONDUCTIVITY<br>40" SPACING |
|                                     |           | 0 1000                                | 0 1000                                |
|                                     | 2" = 100' | 0 1000                                | 0 1000                                |
|                                     | LR 1316   |                                       |                                       |



| SPONTANEOUS POTENTIAL<br>Millivolts | DEPTH     | RESISTIVITY<br>Ohms m <sup>2</sup> /m | CONDUCTIVITY<br>Millimhos/m           |
|-------------------------------------|-----------|---------------------------------------|---------------------------------------|
|                                     |           | INDUCTION RESISTIVITY<br>40" SPACING  | INDUCTION CONDUCTIVITY<br>40" SPACING |
|                                     |           | 0 1000                                | 0 1000                                |
|                                     | 2" = 100' | 0 1000                                | 0 1000                                |
|                                     | LR 1316   |                                       |                                       |

Company: C.E.R. CORPORATION/ERDA  
 Well: COSO SPRINGS #1  
 Field: COSO SPRINGS  
 County: INYO  
 State: CALIFORNIA

Drillers T.D.: 4022  
 Log F.R.: 4017  
 Log T.D.: 4022  
 Elevations:  
 K.B.: 4378.5 D.F.: - G.L.: 4358.5

Dresser Atlas  
 Division of Dresser Industries, Inc.