

BACA PROJECT  
DATA AND REPORTS

WELLS

<u>No.</u>	<u>Transfer Date</u>	<u>Release Date</u>	<u>Title</u>
1.	A	A	Summary sheet for Baca Wells No's 1-3.
2.	A	A	Baca Wells No's 4-16 summary sheet.
3.	A	A	Well summary reports and Drilling Histories-- Baca Wells No's 4-16.
4.	B	B	Lithology logs--Baca Wells No's 4-16.
5.	A	A	Temperature and Pressure Surveys--Baca Wells No's 4-8 and 10-16.
	B	B	Electric logs for Baca Wells No's 10-14.

WELL	ELEV.	T.D.	DRILLED WITH			ENTRIES or (L.C.)	9-5/8" Csg.
			MUD	AIR	AIR/H <sub>2</sub> O		
B-4	5318'	6370'	0-1441'	1441'-T.D.		2115', 2200', 2490', 2591', 3120', 3468', 3710', 4610', 4975', 4995', 5200', 5453', 5640', 5800', 5866'	3100'
B-5A	6320'	6973'	0-700'	700'-T.D.		1226', 2373', 2705', 2795', 3860', 5300'	4400'
B-6	4720'	4810'	0-705'	705'-3715'	3715'-T.D.	1800', (4465')	705'
B-7	4720'	5333'	0-2900' 3135'-T.D.	2900'-3135'			2900'
B-8	4630'	4384'	0-2296' 3020'-T.D.	2296'-3020'			2296'
B-9	4605'	5203'	0-805' 3340'-3600'	805'-3340' 3600'-T.D.		3708', 4077', 5000'	3599'
B-10	4734'	6001'	0-656' 5976'-T.D.	656'-5976'		2622', 3030', 3103', 3200', 3370', 3560', 3713', 4150', 4300?, 4595?, 4760?, 4886?, 5310?, 5480?	4418'
B-11	9065'	6024'	0-3330'	3330'-3959' H <sub>2</sub> O 3959'-T.D. Air/H <sub>2</sub> O		(1973'), (2126'), (2559'), (3507'), (3959' intermittently to T.D.)	3330'
B-12	6400'	9210'	0-3311'	3311'-T.D.		(50-125 PBL/HR. H <sub>2</sub> O Loss from about 6400' to T.D.)	3311'

B-13	3000'	3000' (T.D.) 3000' (T.D.)	3000'	3000'-T.D.	(900'), (1070), (1100'), (1900'), (2420'), (405'), (5170')	3400'
B-14	3000'	3000' (T.D.) 3000' (T.D.)	3000'	3070'-T.D.	(3900'), 4100'	3070'
B-15	3125'	3125' (T.D.) 3125' (T.D.)	3-1525'	3525'-T.D.	(1146'-1154'), (1211'), (1283'), (1460'), (1750'), (1950'), (2040'), (2210'), (2305')	2500'
B-16	3125'	3125' (T.D.) 3125' (T.D.)	3-1525'	4160'-T.D.	(771'), (2160'), (2410'), (2702'), (2880'), (3750')	3905'

7" LINER	450° ISOTHERM	(?) EST/DATE	TOP/BASE BANDELLER	TOP/BASE ANDESITE
3151'-6176'; slots 3036'-6375' None	2800'? (+6518') 6575' (+2745')	5640'-5680'; 5900'-T.D. 4220'-4400'; 4500'; 6840'-6900'; 6840'-T.D.	200'/5090' 450'/6610'	5000'/T.D. 6610'/T.D.
7" sig. 2500' to surf. open hole 2535' to T.D.)	2650' (+6876')	None	500'/4750'	4750'/T.D.
2753'-3111'; slots 3202'-3286' 3371'-3438'; 3715'- <del>3746'</del> 4014'-4117'; 4803'-4881'; 5084'-5112'	5325' (+3395')	2880'; 3460'-T.D.	2000'/3310'	Absent
(2"; 4215' to surface)	2000' (+6630')	2760'-2890'; 3060'-T.D.	580'/3100'	Absent
Abandoned	-	3300'; 3500'	80'/N.R.	N.R.
4478'-6110'; slots 4446'-5594', 5701'-5936'	2450' (+6284')	5100'; 5260'-T.D.	520'/5220'	5220'/5930'
3821'-6924'; slots 3488'-4245', 4882'-6817'; 6899'-6928'	2725'? (+6389')	5300'-6560'	320'/5300'	5300'/6565'
3343'-9111'; slots 3557'-9170' (alternating w/blanks)	2900' (+5530')	5840'-5940'; 6460'-7780'	100'/6460'	6460'/7375'
3840'-4200'; alternating joints	3200' (+6092')	4620'; 4840'-2000'	100'/5710'	5710'/6100'
None	-	5580'; 5720'-6100'	250'/5800'	5800'/6140'
None	-	2720'-2880'; 4760'-4800'; 4880'-T.D.	140'/5300'	N.R.
None	4000' (+5622')	3340'-3660'; 3820'-T.D.	460'/5560'	5560'/6880'