

GL044634

Schlumberger
FOUR-ARM
HIGH RESOLUTION
CONTINUOUS DIPMETER

COMPANY CHEVRON OIL COMPANY
WELL CHEVRON-ATR-GINN NO. 1-13
FIELD WIRLWIND VALLEY AREA
COUNTY LANIER STATE NEVADA
LOCATION CENTER OF THE SE-1/4, Other Services
SE-1/4 OF
Sec. 13 Twp. 31N Rge. 47E
Permanent Datum GL Elev. 4916.9
Log Measured From 13 1/2 ft. Above Form, Datum
Drilling Measured From KB Elev. K.B. 4950.4
D.F. 4926.3

Date 5-22-74
Run No. ONE
Depth-Driller 8500
Depth-Loggert 8493
Log Interval 5492
Top Log Interval 840
Casing-Driller 13-31.66' 812
Casing-Loggert 12-1/4'
Type Fluid in Hole FULL
Dens. 1.00
pH 7.5
Temperature 95
Source Sample 111
2 min. Press. 11.75 @ 82'
3 min. Press. 11.55 @ 82'
4 min. Press. 11.55 @ 82'
5 min. Press. 11.55 @ 82'
6 min. Press. 11.55 @ 82'
7 min. Press. 11.55 @ 82'
8 min. Press. 11.55 @ 82'
9 min. Press. 11.55 @ 82'
10 min. Press. 11.55 @ 82'
11 min. Press. 11.55 @ 82'
12 min. Press. 11.55 @ 82'
13 min. Press. 11.55 @ 82'
14 min. Press. 11.55 @ 82'
15 min. Press. 11.55 @ 82'
16 min. Press. 11.55 @ 82'
17 min. Press. 11.55 @ 82'
18 min. Press. 11.55 @ 82'
19 min. Press. 11.55 @ 82'
20 min. Press. 11.55 @ 82'
21 min. Press. 11.55 @ 82'
22 min. Press. 11.55 @ 82'
23 min. Press. 11.55 @ 82'
24 min. Press. 11.55 @ 82'
25 min. Press. 11.55 @ 82'
26 min. Press. 11.55 @ 82'
27 min. Press. 11.55 @ 82'
28 min. Press. 11.55 @ 82'
29 min. Press. 11.55 @ 82'
30 min. Press. 11.55 @ 82'
31 min. Press. 11.55 @ 82'
32 min. Press. 11.55 @ 82'
33 min. Press. 11.55 @ 82'
34 min. Press. 11.55 @ 82'
35 min. Press. 11.55 @ 82'
36 min. Press. 11.55 @ 82'
37 min. Press. 11.55 @ 82'
38 min. Press. 11.55 @ 82'
39 min. Press. 11.55 @ 82'
40 min. Press. 11.55 @ 82'
41 min. Press. 11.55 @ 82'
42 min. Press. 11.55 @ 82'
43 min. Press. 11.55 @ 82'
44 min. Press. 11.55 @ 82'
45 min. Press. 11.55 @ 82'
46 min. Press. 11.55 @ 82'
47 min. Press. 11.55 @ 82'
48 min. Press. 11.55 @ 82'
49 min. Press. 11.55 @ 82'
50 min. Press. 11.55 @ 82'

Checked in Mud Type or Additional Remarks
Logs Sample No. 111
Depth-Driller 8500
Depth-Loggert 8493
Type Fluid in Hole FULL

Drawn by J. L. H. S. 11-4 HRS
Checked by J. L. H. S. 11-4 HRS
Supervised by J. L. H. S. 11-4 HRS
Reviewed by J. L. H. S. 11-4 HRS
Witnessed by J. L. H. S. 11-4 HRS

Reproduced By
Electrical Log Services
Houston, Texas 77002

REFERENCE K 2637Y

COMPLETION RECORD

SPUD DATE
COMP DATE
DST RECORD
APP. NO.

CASING RECORD
PERFORATING RECORD

ACID, FRAC SHOT

IP
GOR
TF
REMARKS

REPRODUCTION FOR RESALE PROHIBITED

Check in Mud Type or Additional Remarks	Run No.	Tool Type	HOI, S
Logs Sample No. 111	8500	DRILLER	757
Depth-Driller 8500		DRILLER	757
Depth-Loggert 8493		LOGGERT	757
Type Fluid in Hole FULL			

Vertical Displacement	Vertical Displacement	Vertical Displacement	Vertical Displacement
1.54	1307	1187	1000
1.73	1273	1153	966
1.92	1239	1119	932
2.11	1205	1085	898
2.30	1171	1051	864
2.49	1137	1017	830
2.68	1103	983	796
2.87	1069	949	762
3.06	1035	915	728
3.25	1001	881	694
3.44	967	847	660
3.63	933	813	626
3.82	899	779	592
4.01	865	745	558
4.20	831	711	524
4.39	797	677	490
4.58	763	643	456
4.77	729	609	422
4.96	695	575	388
5.15	661	541	354
5.34	627	507	320
5.53	593	473	286
5.72	559	439	252
5.91	525	405	218
6.10	491	371	184
6.29	457	337	150
6.48	423	303	116
6.67	389	269	82
6.86	355	235	48
7.05	321	201	14
7.24	287	167	
7.43	253	133	
7.62	219	99	
7.81	185	65	
8.00	151	31	
8.19	117		
8.38	83		
8.57	49		
8.76	15		
8.95			
9.14			
9.33			
9.52			
9.71			
9.90			
10.09			
10.28			
10.47			
10.66			
10.85			
11.04			
11.23			
11.42			
11.61			
11.80			
11.99			
12.18			
12.37			
12.56			
12.75			
12.94			
13.13			
13.32			
13.51			
13.70			
13.89			
14.08			
14.27			
14.46			
14.65			
14.84			
15.03			
15.22			
15.41			
15.60			
15.79			
15.98			
16.17			
16.36			
16.55			
16.74			
16.93			
17.12			
17.31			
17.50			
17.69			
17.88			
18.07			
18.26			
18.45			
18.64			
18.83			
19.02			
19.21			
19.40			
19.59			
19.78			
19.97			
20.16			
20.35			
20.54			
20.73			
20.92			
21.11			
21.30			
21.49			
21.68			
21.87			
22.06			
22.25			
22.44			
22.63			
22.82			
23.01			
23.20			
23.39			
23.58			
23.77			
23.96			
24.15			
24.34			
24.53			
24.72			
24.91			
25.10			
25.29			
25.48			
25.67			
25.86			
26.05			
26.24			
26.43			
26.62			
26.81			
27.00			
27.19			
27.38			
27.57			
27.76			
27.95			
28.14			
28.33			
28.52			
28.71			
28.90			
29.09			
29.28			
29.47			
29.66			
29.85			
30.04			
30.23			
30.42			
30.61			
30.80			
30.99			
31.18			
31.37			
31.56			
31.75			
31.94			
32.13			
32.32			
32.51			
32.70			
32.89			
33.08			
33.27			
33.46			
33.65			
33.84			
34.03			
34.22			
34.41			
34.60			
34.79			
34.98			
35.17			
35.36			
35.55			
35.74			
35.93			
36.12			
36.31			
36.50			
36.69			
36.88			
37.07			
37.26			
37.45			
37.64			
37.83			
38.02			
38.21			
38.40			
38.59			
38.78			
38.97			
39.16			
39.35			
39.54			
39.73			
39.92			
40.11			
40.30			
40.49			
40.68			
40.87			
41.06			
41.25			
41.44			
41.63			
41.82			
42.01			
42.20			
42.39			
42.58			
42.77			
42.96			
43.15			
43.34			
43.53			
43.72			
43.91			
44.10			
44.29			
44.48			
44.67			
44.86			
45.05			
45.24			
45.43			
45.62			
45.81			
46.00			
46.19			
46.38			
46.57			
46.76			
46.95			
47.14			
47.33			
47.52			
47.71			
47.90			
48.09			
48.28			
48.47			
48.66			
48.85			
49.04			
49.23			
49.42			
49.61			
49.80			
50.00			

TABLE OF VERTICAL DISPLACEMENT IN FEET CORRESPONDING TO VARIOUS HORIZONTAL DISTANCES AND ANGLES OF DIP

Vertical Displacement	Vertical Displacement	Vertical Displacement	Vertical Displacement
1.54	1307	1187	1000
1.73	1273	1153	966
1.92	1239	1119	932
2.11	1205	1085	898
2.30	1171	1051	864
2.49	1137	1017	830
2.68	1103	983	796
2.87	1069	949	762
3.06	1035	915	728
3.25	1001	881	694
3.44	967	847	660
3.63	933	813	626
3.82	899	779	592
4.01	865	745	558
4.20	831	711	524
4.39	797	677	490
4.58	763	643	456
4.77	729	609	422
4.96	695	575	388
5.15	661	541	354
5.34	627	507	320
5.53	593	473	286
5.72	559	439	252
5.91	525	405	218
6.10	491	371	184
6.29	457	337	150
6.48	423	303</	