

BALTAZOR KGRA AND VICINITY, NEVADA  
Geothermal Reservoir Assessment Case Study  
Northern Basin and Range Province

FINAL REPORT

1 October 1978 - 31 January 1983

T.C. WRIGHT

Earth Power Production Company  
970 East 4800 South  
Salt Lake City, Utah 84117

Prepared for the  
U.S. DEPARTMENT OF ENERGY  
NEVADA OPERATIONS OFFICE  
Under Contract DE-AC08-79ET27007

## DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Printed in the United State of America

Available from:

National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Road  
Springfield, Virginia 22161

Price: Printed copy \$ \_\_\_\_\_  
Microfiche \$3.50

Price of the printed copy is determined by the number of pages in the report. Since prices are revised periodically, contact the Contracting Officer for current prices.

TABLE OF CONTENTS

	Page
ABSTRACT .....	1
Introduction' .....	2
Geology .....	5
Geochemistry .....	6
Geophysics .....	10
Temperature Gradient Holes .....	13
Deep Test Hole .....	24
References .....	40
Appendix A. Data on Open-File at UURI .....	42

TABLE OF ILLUSTRATIONS AND TABLES

	Page
Figure 1. Index map.....	3
Figure 2. Land status map.....	4
Figure 3. Geochemical data map.....	8
Figure 4. Map, sulfate as a percentage of total dissolved solids.....	9
Figure 5. Aeromagnetic map.....	11
Figure 6. Microearthquake survey station locations and epicenters.....	12
Figure 7. Gravity, dipole-dipole and SP survey line locations.....	14
Figure 8. Complete Bouguer gravity anomaly map.....	15
Figure 9. Residual Bouguer gravity anomaly map.....	16
Figure 10. Gravity interpretation plan map.....	17
Figure 11. Composite gravity, resistivity and SP interpretation map, Baltazor KGRA .....	18
Figure 12. Interpreted (from geophysics) geologic cross-section along Line B2, Baltazor KGRA.....	19
Figure 13. Composite gravity, resistivity, and SP interpretation map, McGee/Painted Hills area.....	20
Figure 14. Interpreted (from geophysics) geologic cross-section along Line M2, McGee/Painted Hills area.....	21
Figure 15. Temperature gradient map.....	23
Figure 16. Well completion schematic, Baltazor 45-14.....	34
Figure 17. Generalized stratigraphic column, Baltazor 45-14.....	35
Figure 18. Temperature surveys dated 10/31/82, and 11/25/82, Baltazor 45-14.....	36
Figure 19. Temperature survey dated 2/3/83, Baltazor 45-14.....	39

TABLE OF ILLUSTRATIONS AND TABLES CONTINUED

	Page
Plate I. Geologic and alteration maps, Baltazor Hot Springs and Painted Hills Thermal areas.....(in pocket)	
Table I. Logging history for Baltazor 45-14.....	25
Table II. Drilling history for Baltazor 45-14.....	27
Table III. Heat flow data, Baltazor 45-14.....	37

## ABSTRACT

The Baltazor KGRA and McGee/Painted Hills geothermal prospects are located in northern Humboldt County, Nevada along the northwestern margin of the Basin and Range province. Earth Power Production Company (EPPC) began exploration of the prospects in 1977. EPPC continued its program as a Geothermal Reservoir Assessment Case Study funded in part by the U.S. Department of Energy under Contract DE-AC08-79ET27007.

Geologic work has included a literature search and reconnaissance photogeologic mapping study and then detailed field geologic and alteration mapping. A groundwater sampling program and soil mercury survey were the geochemical techniques used. Geophysics consisted of a microearthquake study; aeromagnetic mapping; and a gravity, electrical resistivity and self-potential study.

Exploration drilling included 27 shallow temperature gradient holes, four intermediate-depth gradient wells and one 3703-foot deep test, Baltazor 45-14. The deep test penetrated Miocene rhyolite, andesite, basalt and andesitic basalt flows before excessive hole deviation forced an end to drilling and completion as a deep observation well. A temperature survey two weeks after completion obtained a 119.7°C (247.4°F) reading at survey total depth, 1110m (3640 feet).

## Introduction

The Baltazor Hot Springs KGRA and McGee Mountain/Painted Hills geothermal area are located in northern Humboldt County, Nevada along the northwestern margin of the Basin and Range province (see Figs 1 and 2). The Baltazor prospect contains about 40 sections under lease to subsidiaries and affiliates of Grace Geothermal Corporation. The McGee area contains about 50 sections under lease to the same companies. Earth Power Production Company (EPPC) of Tulsa, Oklahoma is operator.

EPPC began geothermal exploration at Baltazor and McGee in 1977 with a groundwater sampling survey (Klein and Koenig, 1977) and a microearthquake study (Senturion Sciences, 1977). A geologic literature search and photogeologic mapping study (Gardner and Koenig, 1978) followed in 1978 along with a program of shallow gradient hole drilling (EPPC, 1979). An aeromagnetic survey (Scintrex Mineral Surveys, 1972) and gravity maps (Plouff et al., 1976; Peterson and Hoover, 1977) completed the 1978 data base.

EPPC submitted a proposal in May 1978 in response to DOE RFP No. ET-78-R-08-0003 to provide this existing data and new data as one of the Geothermal Reservoir Assessment Case Studies (Northern Basin and Range Province). DOE awarded a contract to EPPC effective October 1, 1978. New data was to be delivered to DOE in three phases. In Phase I, EPPC drilled and ran temperature surveys in 4 intermediate depth (about 460m=1500 feet) temperature gradient holes in 1979. In Phase II, completed in January, 1983, EPPC drilled one deep exploratory hole, 45-14, in the Baltazor area to a depth of 1129m (3703 feet). EPPC has delivered drill cuttings, mud logs and a suite of geophysical logs to DOE for this well.




FIGURE I  
INDEX MAP

(from Edquist, 1981)






Figure 2

<b>EARTH POWER PRODUCTION COMPANY</b> TULSA, OKLAHOMA	
<b>LAND STATUS</b>	
BALTAZOR-McGEE GEOTHERMAL PROSPECTS HAMBOLDT COUNTY, NEVADA	
DATE: _____ SCALE: _____	DRAWN BY: SURVEY: _____

DATE	_____
SCALE	_____
DRAWN BY	_____
SURVEY	_____

Steel tubing 2<sup>3</sup>/<sub>8</sub> inches in diameter was run into the hole to 1110m (3640 feet) and filled with water. A temperature of 119.7°C (247.4°F) was measured at 1110m on February 3, 1983. Phase III, consisting of flow tests if a productive zone was encountered, was not performed.

All of the data delivered to the DOE are on open file with the Earth Science Laboratory, University of Utah Research Institute, Salt Lake City (see Appendix A).

### Geology

Gardner and Koenig's 1978 literature search and photo-geologic mapping study was followed by additional geologic and hydrothermal alteration mapping under a DOE contract (Hulen, 1979). The following discussion is based on the latter study.

Plate I (Hulen, 1979) is a geologic map of the Baltazor and Painted Hills/McGee areas. Cretaceous diorite and quartz diorite intrude Permian to Triassic eugeosynclinal meta-sedimentary and metavolcanic rocks in the Baltazor area. A thick sequence of Miocene to Pliocene volcanic and volcanoclastic rocks overlies the Permian to Triassic and intrusive rocks. Only the younger sequence crops out in the McGee area, and only the later part of the sequence has been correlated with rocks in the Baltazor area.

Moderate-to high-angle, north-to northeast-trending Basin and Range faults probably control the ascent of thermal fluids near Baltazor Hot Springs. The hot springs location may be controlled by an intersection with near-vertical, northwest-trending faults, the second prominent fault set in the

area. Quaternary landslides dominate the structural geology of the Painted Hills/McGee area.

Baltazor Hot Springs has measured temperatures of 76°C to 98°C (169° to 208°F.; Klein and Koenig, 1977). Near-surface gradients approach 290°C/km (16°F/100 feet). There are no thermal springs in the Painted Hills/McGee area, but near-surface gradients of about 400°C/km (22°F/100 feet) have been measured and warm ground and intermittent fumeroles have been reported (Gardner and Koenig, 1978).

Several different styles and ages of hydrothermal alteration and mineralization are found at Baltazor and McGee. The oldest phenomenon consists of copper-bearing quartz veins emplaced in pre-Tertiary rocks prior to Cenozoic volcanism. Argillization, silification, hematization and mercury mineralization are spread throughout the Painted Hills; this alteration is probably pre-Pleistocene. Alteration at Baltazor Hot Springs consists of small calcite-bearing opaline sinter deposits. Siliceous sinter deposits indicate reservoir temperatures of at least 180°C (356°F) in the past at Baltazor. The hot spring is not presently precipitating silica.

No young rhyolitic volcanics are present at Baltazor or McGee. These areas are located within the Battle Mountain zone of high heat flow (Sass et al., 1971). These two facts suggest that the thermal phenomena at Baltazor/McGee are due to deep circulation along faults rather than to a shallow body of silicic magma.


### Geochemistry

GeothermEx, Inc. performed a hydrochemical study of therm-

al areas in 1977 (Klein and Koenig, 1977). The goals of the survey were " to use integrated hydrologic, hydrochemical, and geologic data to describe the region's water-circulation systems and to predict as closely as possible the temperature and composition of deep thermal fluids, characteristics and location of possible aquifer host rocks, volume of recharge to the deep and shallow systems and potential sustained annual yield."

Twenty-six water samples and three gas samples from hot springs were collected and analyzed. Figures 3 and 4 are maps depicting, respectively, geochemical data and sulfate as a percentage of total dissolved solids. Silica and Na-K-Ca geothermometers indicated a maximum surface temperature for Baltazor Hot Springs of about 160°C (320°F). A temperature less than about 135°C (275°F) appeared to be unlikely. While its sub-boiling temperature made it tempting to hypothesize that Baltazor Hot Springs is a mixed water, no cool component could be deduced that would behave consistently with respect to all the major solutes or the Na-K-Ca geothermometer. Baltazor water, therefore, is probably cooled by conduction as it rises from depths of a kilometer or more. High fluoride content points to an acidic igneous reservoir host rock, either Tertiary dacite-rhyolite or Mesozoic granitics, or at shallower depths, basalts.

A well two miles northeast of the Painted Hills Mine fumarole in the McGee area produces a cool water very similar to Baltazor Hot Springs. Klein and Koenig postulate this to be a thermal water that rises along the McGee Mountain fault and then flows down to the east within dipping sediments. Probably this water derives from a reservoir in rocks like those of the Baltazor reservoir at a similar depth.



**EARTH POWER  
PRODUCTION COMPANY**  
TULSA, OKLAHOMA

**GEOCHEMICAL DATA**

**BALTATOR-McGEE  
GEOTHERMAL PROSPECTS**  
HAMBOLDT COUNTY, NEVADA

DATE: SEPTEMBER 22, 1970      DRAWN BY: J.L. GIBSON  
SCALE: 1" = 1 MILE      SURVEY:

- PLATE: SELECTED SYMBOLS AND GENERAL CHARACTERISTICS OF GEOTHERMAL PROSPECTS
- LOCATIONS**
- WELL
  - SPRING
  - PLANNED WELL
  - UNDEVELOPED WELL POINT
- CONCENTRATION**
- APPROXIMATELY EQUAL
  - 1 1/2 TIMES BY WEIGHT CONCENTRATION
  - 3 1/2 TIMES
  - 5 TO 10 TIMES
  - 20 MORE THAN 10 TIMES
- Source: GEOTHERMAL SURVEY, SECKHOFF, 1977





Figure 3



**NOTE:**  
 1. SULFATE SHOWN AS PERCENT OF TOTAL DISSOLVED SOLIDS.  
 2. CONTOUR INTERVAL: 5% T.D.S.  
 3. DATA SOURCE - GEOCHEMICAL SURVEY BY GEOTHERMEX, INC. / FALL 1977

**EARTH POWER PRODUCTION COMPANY**  
 TULSA, OKLAHOMA

**SULFATE MAP**

**BALTAZOR-MAGEE GEOTHERMAL PROSPECTS**  
 HUMBOLDT COUNTY, NEVADA

DATE: 1977  
 SCALE: 1:62,500

Figure 4

Soil samples were collected from 14 sections surrounding Baltazor Hot Springs during February, 1980 and analyzed for mercury and arsenic (Blair, 1980). The 171 samples were taken on a grid with 1000-foot centers, 2000-foot centers in the peripheral area. No contour maps or interpretation of the results seems to have been made. The analyses do show two apparent maxima of mercury content: A peak value of 2.8 ppm about 1.3 miles northeast of the later deep test hole, 45-14, along the Pueblo Range front fault; and 1.4 ppm in the N $\frac{1}{2}$ , Section 22, T. 46 N., R. 28 E. along the west side of the Pueblo Mountains ridgeline.

### Geophysics

Scintrex Mineral Surveys flew aeromagnetic coverage of the Baltazor-McGee area in 1972 at a constant barometric elevation of 2.74km (9000 feet; see Figure 5). Since the survey is regional in scope and contours reflect topography primarily, the survey has not proved very useful for interpretation of the geothermal system (Edquist, 1981).

Senturion Sciences, Inc. deployed two 6-station, 9-km diameter pentagonal seismometer arrays in the Baltazor-McGee area in June and July, 1977 (Senturion Sciences, 1977). The purpose was to define heat sources as indicated by microearthquakes and to determine relative crustal movements. Three microearthquake clusters were detected, the Denio, Thousand Creek and Craine Creek clusters (Figure 6).

First motions for the Denio swarm were compatible with a steeply dipping, north-northeast trending normal fault plane bounding the Pueblo Mountains west of Baltazor Hot Springs. The block on the west side of the fault moved upward relative to the eastern valley. Relative crustal movements could not be deduced from the Thousand Creek and Craine Creek clusters.




FIGURE 6 NW NEV 1 and 2 station locations and epicenters for microearthquakes detected with both six-station surveys. (from Senturion Sciences, Inc., 1977)




The swarms may have resulted in part from thermal stresses induced by high heat flows; normal tectonic stresses may also have been responsible for the microearthquakes.  $V_p/V_s$  ratios for the combined Denio and Thousand Creek data gave an anomalous (low) Poisson's ratio, possibly indicating voids filled with steam.

Edquist (1981) compiled and interpreted gravity, electrical resistivity and self-potential data for the Baltazor and McGee areas under contract to the DOE. Edquist himself collected gravity data from 194 stations and added this to 90 stations collected previously (Peterson and Hoover, 1977; Plouff et al, 1976). Half the data were taken along survey lines (Figure 7 , Figure 8 is a complete Bouguer gravity anomaly map; Figure 9 is a residual Bouguer gravity anomaly map. Cross section Figure 10 indicates that Baltazor Hot Springs appears to be controlled by recent faults that trap aquifers in the Steens Basin. Figure 10 is a gravity interpretation map.


Edquist also models and interprets pole-dipole resistivity and self-potential data collected during Geophysical Surveys, Inc. (1980) on contract to EPPC. Profiles of resistivity data were collected for a total of 108 line-km. About 38 line-km of SP data were collected along eight profiles. Figures 11 and 12 present interpretations of these data for the Baltazor area; Figures 13 and 14 do so for the Painted Hills/McGee area.

#### Temperature Gradient Holes

EPPC drilled 27 shallow gradient holes, most to a depth of about 90m (300 feet), during the summer of 1977. The



(from Edquist, 1981)







FIGURE 12  
 INTERPRETED GEOLOGIC CROSS-SECTION  
 ALONG LINE B2  
 BALTAZOR HOT SPRINGS KGRA  
 HUMBOLDT COUNTY, NEVADA

(from Edquist, 1981)



(from Edquist, 1981)




FIGURE 14  
 INTERPRETED GEOLOGIC CROSS-SECTION  
 ALONG LINE M2  
 PAINTED HILLS AREA  
 HUMBOLDT COUNTY, NEVADA  
 (from Edquist, 1981)

mum gradient measured at Baltazor was 290°C/km (15.9°F/100 feet); the maximum at McGee was about 455°C/km (25°F/100 feet). Figure 15 is a temperature gradient contour map based on these holes.

Four intermediate-depth gradient holes were drilled in 1979 ( see plate I ) . Two intermediate depth holes were drilled near the center of the Baltazor anomaly near the range front fault. Baltazor 1500-1 was drilled about half-way between the hot spring and the range front. This hole went through the hot water aquifer at about 60m (200 feet), cooled to about 82°C (180°F) to 210m (700 feet), then slowly began to warm again with a bottom hole temperature of 90.5°C (195°F) at 467m (1532 feet).

The second intermediate depth hole, Baltazor 1500-2 was drilled about a mile southwest of the first hole at a location very near the range front of the Pueblos. This fault cannot be accurately traced in this area due to the large slump blocks that complicate the surface geology. Presumably, the hole penetrated the main fault zone and entered the foot wall at less than 145m (500 feet) unless this fault is much steeper than thought. The hole encountered a zone of 41°C (105°F) water at 76m (250 feet), then cooled to a low of 37°C (98°F) at 150m (475 feet). From 150m to 380m (475 to 1250 feet), the hole warmed to 57°C (135°F), then began increasing in temperature at a rate of about 200°C/km (11°F/100 feet), to a bottom hole temperature of 68°C (154°F) at 434m (1425 feet).

Two intermediate holes also were drilled in the McGee area. McGee 1500-1 was drilled in the area of warm ground where very high temperatures were measured in shallow holes. This hole heated rapidly to a temperature of 117°C (242°F)

at 101m (330 feet), cooled to about 104°C (220°F) at 183m (600 feet), then stayed roughly isothermal to a bottom hole temperature of 103°C (217°F) at 455m (1493 feet). The hole was drilled for the most part without returns but apparently the bulk of the hole was in faulted Miocene sedimentary strata.

McGee 1500-2 was drilled east of the fault system at the foot of the upthrown McGee Mountain block. This hole increased in temperature throughout its depth to a bottom hole temperature of 93°C (200°F) at 509 m (1670 feet). The temperature profile shows a slight break in gradient at about 290m (950 feet), possibly due to a change in thermal conductivity. The gradient at the bottom of the hole is about 110°C/km (6°F/100 feet).

#### Deep Test Hole

Southwest Drilling and Exploration Rig #111 moved on site September 21, 1982. Baltazor 45-14 was spudded September 24 in the NE $\frac{1}{4}$ NE $\frac{1}{4}$ SW $\frac{1}{4}$ , Section 14, T. 46N., R. 28E. and drilled to 771m (2529 feet) by October 25. Very slow penetration rates and hole deviation problems dictated use of a larger rig. Rig #111 was moved off the hole, which was temporarily shut in.

On December 21, 1982, Calvert Western Rig #5 began moving on site, reamed the hole from 6 $\frac{1}{2}$  inches to 8 $\frac{1}{2}$  inches and started making new hole on January 6, 1983. Hole deviation was again severe, culminating in a 24° measurement at 1078m (3537 feet). On January 15, Gearheart-Owens ran a full suite of geophysical logs to a depth of 1100m (3609 feet). (See Table I.) Drilling was continued slowly to a total depth of 1129m (3703 feet), and on January 19, 2 $\frac{3}{8}$ -inch tubing was set at 1125m (3689 feet) and filled with water in prep-



Table I.  
 Logging History for Well 45-14  
 Baltazor KGRA, Nevada

<u>Date</u>	<u>Type of Log</u>	<u>Logged Interval</u>	<u>Total Depth</u>
10-01-82	Dual Induction Laterolog-GO	39-418'	419'
10-01-82	Compensated Neutron-GO	39-418'	419'
10/01/82	Gamma Ray-GO	39-418'	419'
10/01/82	Caliper-GO	39-418'	419'
10/01/82	Borehole Compensated Sonic-GO	39-409'	419'
10/01/82	Integrated Travel Time-GO	39-409'	419'
10/01/82	Temperature-GO	39-418'	419'
10/31/82	Temperature-Southwest	60-2430'	2529'
11/25/82	Temperature-Southwest	80-1567'	2529'
1/15/83	Compensated Neutron-GO	402-3609'	3610'
1/15/83	Gamma Ray-GO	402-3609'	3610'
1/15/83	Caliper-GO	402-3609'	3610'
1/15/83	Borehole Compensated Sonic-GO	402-3609'	3610'
1/15/83	Integrated Travel Time-GO	402-3609'	3610'
2/03/83	Temperature-Southwest	40-3640'	3703'

(note: All logs on open-file, ESL/UURI)

aration for a final temperature survey. Table II is a complete drilling history for 45-14. Figure 16 is a well completion schematic.

Lost circulation was not the major problem that had been feared. Circulation was lost briefly at 95m (312 feet), 788 (2584 feet; 80 bbl.) and 1082m (3550 feet; 80 bbls.). The major problem was deviation of the hole from vertical, a problem that worsened as drilling proceeded. Weight on the bit was kept relatively low but with little effect. We hypothesize that the hole encountered a range-front fault bordering the east side of the Pueblo Mountains that deflected drilling for most of the depth of 45-14.

Drill cutting samples were collected at 3m (10-foot) intervals; they may be examined at the Geothermal Sample Library, University of Utah Research Institute, (UURI) Salt Lake City. (Cuttings for 15 shallow gradient holes and 3 intermediate-depth holes also are on file.) Figure 17 is a generalized stratigraphic column for 45-14; detailed mud logs are on open-file at UURI.

Two open-hole temperature surveys, run after the hole was drilled to 771m (2529 feet), are shown in Figure 18. Thermal conductivity measurements on 26 drill cuttings samples permitted calculation of heat flow values for selected intervals (Table III). The gradient value in the 493m to 585m interval (1440 to 1920 feet) of  $155^{\circ}\text{C}/\text{km}$  ( $8.48^{\circ}\text{F}/100$  feet) is probably a good approximation to the true conductive gradient. The associated heat flow of 5.3 HFU probably characterizes well the true conductive heat flow (Southwest Drilling and Exploration, 1983a).

Table II.  
**DRILLING HISTORY**

HOLE NO: 45-14

DATE	DEPTH	SUMMARY OF OPERATIONS
9/21/82	0- 0	Move rig to site. Build road and pad. Dig one mud pit and rig up.
9/22/82	0- 0	Continue to rig up and dig second mud pit.
9/23/82	0- 0	Finish digging mud pits. Haul water and mix mud. Send flat bed truck to pick up casing.
9/24/82	0- 36	Stir up mud pits. Spud hole at 7:30 am with 17 1/2" bit and drill to 36' in alluvial fan deposits. Set 12 1/4" surface casing to 36'. Mix cement and pump down outside of casing. Build and install flowline.
9/25/82	36- 190	Make up 8 3/4" bottom hole assembly and drill to 147'. Trip to check bit. Run in hole with 9 7/8" bit and ream from 36' to 147'. Drill to 190' with 9 7/8" bit. Drilling in alluvial fan deposits to 180', rhyolite to 190'.
9/26/82	190- 280	Drill to 200'. Trip to check bit and adjust rotary table clutch linkage. Drill to 207'. Trip to lay down stabilizer and drill to 280' in rhyolite with 9 7/8" bit.
9/27/82	280- 394	Drill to 312' and encounter lost circulation zone. Loose 1/2 pit of mud. Mix mud and LCM. Regain circulation. Drill to 394' in rhyolite.
9/28/82	394- 407	Mix mud. Drill to 407' in rhyolite. Trip out of hole and make up 12 1/4" hole opener. Ream hole from 36'.
9/29/82	407- 421	Continue to ream hole with 12 1/4" hole opener to 407'. Trip out to lay down hole opener. Clean mud pits and mix mud. Run in hole with 9 7/8" bit and drill to 417'. Trip to lay down stabilizer. Run in hole and drill to 421' in rhyolite.
9/30/82	421- 442	Drill to 442' in rhyolite. Trip out of hole. Make up hole opener. Run in hole and ream hole with 12 1/4" opener from 407'.

DATE	DEPTH	SUMMARY OF OPERATIONS
10/01/82	442- 442	Continue to ream hole with 12 1/4" hole opener to 418'. Pull out of hole. Gearhart logging hole. Run 9 5/8" casing. Unable to get casing past 320'. Pull casing out of hole.
10/02/82	442- 442	Continue to pull casing out of hole. Make up stacked hole opener. Run in hole with 12 1/4" stacked hole opener. Ream to straighten hole from about 280'.
10/03/82	442- 442	Continue to ream hole to straighten down to 403'. Pull out of hole and lay down pipe. Run 9 5/8" casing to 402'. Cement casing; good returns. Wait on cement.
10/04/82	442- 442	Wait on cement. Dig cellar for ROPE. Cut off casing, weld on well head and install ROPE. Test ROPE; passes test. Clean mud pits. Make up 8 3/4" down hole assembly.
10/05/82	442- 525	Run in hole with 8 3/4" bit. Tagged cement at 369'. Condition mud. Drill to formation 428'. Trip to change to 6 3/4" bit and stablizer. Drill in altered rhyolite to 525'. 500' to 520' is vesicular rhyolite and ash tuff.
10/06/82	525- 649	Drill with 6 3/4" bit to 649'. Drilling in vesicular rhyolite to 570', and rhyolite to 610'. Lithology change at 610' to andesite where drilling slows.
10/07/82	649- 736	Drill with 6 3/4" bit to 660'. Trip to change bit and drill to 736' in andesite.
10/08/82	736- 750	Drill to 750'. Pull out of hole to switch from mud to air. Run in hole. Encounter too much water (~200 GPM). Pull out of hole. Switch to mud and ream hole.
10/09/82	750- 881	Continue to ream hole with 6 3/4" bit to 750'. Trip to change bit. Drill to 881'. Lithology change at 870' to basalt.
10/10/82	881-1018	Drill to 940' in basalt, to 970' in ash flow tuff, to 990' in basalt, to 1018' in basalt/clay. Trip out of hole at 990' to clean 6 3/4" bit and put in jets.
10/11/82	1018-1228	Continue to drill with 6 3/4" bit from 1018' to 1228' in basalt.

DATE	DEPTH	SUMMARY OF OPERATIONS
10/12/82	1228-1483	Drill from 1228' to 1483' with 6 3/4" bit. Drilling in basalt with blue clay.
10/13/82	1483-1612	Drill with 6 3/4" bit to 1490' (still in basalt with blue clay). Thin mud and drill to 1570' in basalt. Trip out of hole to check bit. Clean mud pits and run maintenance on rig. Mix mud and run in hole with 6 3/4" bit. Drill to 1612' in basalt.
10/14/82	1612-1750	Drill with 6 3/4" bit to 1750' in basalt. Circulate to clean hole and drop drift tool (bad run). Run in hole and mix mud.
10/15/82	1750-1804	Drop drift tool again (6 deg off). Trip out of hole. Maintenance. Mix mud and run in hole with 6 3/4" bit, drill in basalt to 1804'. Drilling with reduced weight on bit to straighten hole.
10/16/82	1804-1872	Drill with 6 3/4" bit from 1804' to 1872' in basalt with ash/tuff.
10/17/82	1872-1913	Drill with 6 3/4" bit to 1895'. Mix mud and continue down to 1913' in basalt. Drop drift tool (3.25 deg off). Pull out of hole. Run maintenance on rig.
10/18/82	1913-1954	Rig maintenance. Run in hole with new 6 1/2" bit. Drill to 1920'. Mix mud and continue to 1954' in basalt.
10/19/82	1954-2038	Drill to 1994' with 6 1/2" bit. Circulate and drop drift tool (5.75 deg off). Pull out of hole, maintenance, run in hole. Drill ahead to 2038' with 6 1/2" bit in basalt.
10/20/82	2038-2132	Drill ahead to 2132' in basalt with 6 1/2" bit. At 2064' added water to pit to reduce viscosity of mud. Rig maintenance at 2114'.
10/21/82	2132-2184	Drill ahead to 2184' in basalt with 6 1/2" bit. Open 3rd mud pit and mix mud. Pull out of hole - 10 buttons missing from bit. Install new 6 1/2" journal button bit, mix mud and run in hole. Circulate and run wireline deviation survey (3.75 deg off). Pull out of hole - plugged float. Clean mud pump and lines.
10/22/82	2184-2268	Run in hole. Mix and condition mud. Drill with 6 1/2" bit to 2268' in basalt to 2190', to 2268' in andesitic basalt. Water added to mud pits at 2194', 2206', and 2254'.

DATE	DEPTH	SUMMARY OF OPERATIONS
10/23/82	2268-2375	Drill ahead with 6 1/2" bit to 2300' mixing mud at 2294'. Run wireline deviation survey at 2300' (2.25 deg off). Drill ahead to 2375' mixing mud at 2354'. Drilling in andesitic basalt 2268' to 2375'.
10/24/82	2375-2462	Maintenance (repair pump clutch yoke). Drill ahead to 2400'. Circulate and run wireline deviation survey (2.00 deg off). Drill ahead to 2434'. Maintenance (change hoisting line). Drill ahead to 2462', mixing mud at 2454'. Andesitic basalt 2375' to 2462'.
10/25/82	2462-2529	Drill ahead to 2500' with 6 1/2" bit. Circulate and run wireline deviation survey (bad run). Drill ahead to 2513', circulate, and run survey again (5.00 deg off). Drill to 2529' in andesitic basalt. Pull out of hole.
10/26/82	2529-2529	Maintenance (clean and re-install hoist line clutch). Clean mud pits and mix mud. Maintenance (change battery on rig, air line on draw works, and check gear boxes). Run in hole and mix mud. Problems with hoisting line clutch, will not pull pipe. Pull out of hole.
10/27/82	2529-2529	Maintenance on hoisting line clutch.
10/28/82	2529-2529	Make up 8 5/8" hole opener. Run in hole to 475'. Stir mud pits and mix mud. Ream hole from 475' to 758'.
10/29/82	2529-2529	Ream hole with 8 5/8" hole opener from 758' to 796'.
10/30/82	2529-2529	Pull out of hole and lay down pipe. Pick up and load equipment.
10/31/82	2529-2529	Run temperature survey on hole. TD = 2430'.
11/01/82	2529-2529	Rig down. Move rig to Denic Junction. Remove mud from pits.

DATE	DEPTH	SUMMARY OF OPERATIONS
11/02/82- 12/20/82	2529-2529	Well shut in with BOP installed, waiting on rig. Calvert Western Exploration Co. Franks 400 Series Explorer III "Rocket" moved on hole as follows:
12/21/82	2529-2529	Dig out for cellar and unload truck.
12/22/82	2529-2529	Dig out cellar and for mud pits.
12/23/82	2529-2529	Dig out for mud pits where dozer missed.
12/24/82	2529-2529	Unload trucks and set mud pit.
12/28/82	2529-2529	Rig up and unload trucks. Put derrick on unit.
12/29/82	2529-2529	Rig up -- board in cellar.
12/30/82	2529-2529	Rig up: rework some areas of location; set unit, sub, doghouse, mudpit, mud pump.
12/31/82	2525-2529	Rig up: rework some areas of location with backhoe; set pipe baskets, mudpump, walk and racks.
1/01/83	2529-2529	Rig up.
1/02/83	2529-2529	Rig up: nipple up, weld on Bradden head, mix mud.
1/03/83	2529-2529	Pick up bit and B.H.A. Clean out bridges and condition mud. Ream from 456 to 754 to 8½". Run deviation survey: 9° at 723'.
1/04/83	2529-2529	Reaming 8½" hole to 1560'. Run deviation surveys: 9 3/4° at 824', 9 3/4° at 916', 8½° at 1008', 8° at 1100', 7 3/4° at 1192", 8½° at 1284', 8½° at 1376', 8½° at 1499'.
1/05/83	2529-2529	Reaming 8½" hole to 2164. Run deviation surveys: 7½° at 1591', 4½° at 1990', 3° at 2113'.
1/06/83	2529-2540	Reaming 8½" hole to 2529'. Deviation 2½° at 2237', 5° at 2391'. Trip out -- I.B.S. 60' off bottom. Change B.H.A., pick up 2 drill collars and trip in. Reaming, drilling new hole to 2540'.

DATE	DEPTH	SUMMARY OF OPERATIONS
1/07/83	2540-2682	Drilling 8½" hole in andesitic basalt. Deviation 9½° at 2583'. Lost 80 bbls mud at 2584, mix LCM. Deviation 10½° at 2636', 11 3/4° at 2667'. Trip out @ 2655' to change B.H.A., trip in. Drilling to 2682'.
1/08/83	2682-2773	Drilling 8½" hole in andesitic basalt. Deviation 12° at 2696', 11° at 2727', 12¼° at 2758'.
1/09/83	2773-2829	Drilling 8½" hole in andesitic basalt. Deviation 12° at 2789', 12° at 2819.
1/10/83	2829-2923	Drilling 8½" hole in andesitic basalt. Deviation 12° at 2851', 12° at 2881', 12¼° at 2912'. Trip out to change B.H.A., trip in.
1/11/83	2923-3081	Drilling 8½" hole in basalt. Deviation 12½° at 2950', bottom-hole temperature 148°F; deviation 12¼° at 2981', B.H.T. 160°F.
1/12/83	3081-3295	Drilling 8½" hole in basalt and, in 3090-3140' and 3180-3210' intervals, welded tuff. Trip out at 3260' to change bit, trip in. Drilling to 3295'.
1/13/83	3295-3551	Drilling 8½" hole in basalt and, to 3460', welded tuff. Deviation 24° at 3537'. Lost 80 bbls mud at 3550'. Trip out 18 stands drill pipe, circulate mud, add LCM.
1/14/83	3551-3588	Circulate and condition mud. Trip out and lay down B.H.A. and 6 drill collars. Trip in with new 8½" bit and 6 drill collars. Drill basalt to 3588'.
1/15/83	3588-3610	Drilling 8½" hole in basalt to 3610'. Condition hole for logs. Trip out and rig up for logging. Run Gearheart-Owens logs, rig down loggers.
1/16/83	3610-3676	Drilling 8½" hole in basalt.
1/17/83	3676-3703	Drilling 8½" hole in basalt. Condition hole to run tubing. Trip out 30 stands D.P.



DATE	DEPTH	SUMMARY OF OPERATIONS
1/18/83	3703-3703	Circulate and condition hole for tubing. Trip in 30 stands D.P. to bottom -- no fill. Circulate, trip out and lay down D.P., collars. Break kelly, nipple down. Rig up to run tubing. Run 10 joints 2 3/8" tubing.
1/19/83	3703-3703	Run 116 joints tubing, set at 3689', fill with water. Wash pumps and pits, rig down.
1/20/83	3703-3703	Rig down, move rig to Denio.
1/21/83	3703-3703	Rig down, move rig to Denio. Fence reserve pit.




Figure 16. Well Completion Schematic, Baltazor 45-14.





Figure 17. Generalized Stratigraphic Column, 45-14.

Sources: Southwest Drilling and Exploration, 1983a;  
ExLog Smith mud logs (on open-file, UURI)

# TEMPERATURE (°F)



(from Southwest Drilling and Exploration, 1983a)

TABLE III.  
HEAT FLOW DATA  
BALTAZOR HOT SPRINGS  
HOLE NO: 45-14

RUN NUMBER	TOTAL DEPTH (FEET)	BOTTOM HOLE TEMP (DEG F)	GRADIENT A (DEG F/100 FT)*	GRADIENT INTERVAL (FEET)	CALC SURF TEMP (DEG F)**	GRADIENT (DEG F/100 FT)+	THERMAL CONDUCTIVITY (TCU)++	HEAT FLOW (HFU)}
1	2430	223.77	6.9	800-1280	72.1	4.93	3.6(6)	3.2
				1440-1920	22.6	8.48	3.4(5)	5.3
				1920-2120	-25.7	11.00	3.5(2)	7.0
2	1567	161.41	6.8	600-900	90.5	2.25	4.0(4)	1.6
				900-1400	56.9	6.08	3.4(5)	3.8
				1420-1567	30.8	8.26	3.1(1)	4.7

\* Gradient A = The bottom hole temperature minus an estimated mean annual surface temperature of 55 degF divided by the total depth.

\*\* Extrapolated surface temperature.

+ Least-squares geothermal gradient calculated over the gradient interval.

++ TCU = mcal/cm-sec-degC. Number of thermal conductivity samples for each interval in parentheses.

} HFU = microcal/sq-cm-sec.

(from Southwest Drilling and Exploration, 1983a)

A final temperature survey was made on February 3, 1983 after the 2<sup>3</sup>/<sub>8</sub>-inch tubing was set (Figure 19). Gradients over the 493m to 585m and 585m to 646m intervals closely matched those measured earlier. The gradient for the 902m to 1012m interval (2960 to 3320 feet) measured only 25.7°C/km (1.41°F/100 feet). Temperature at the survey total depth of 1110m (3640 feet) was 119.7°C (247.4°F). (Southwest Drilling and Exploration, 1983b). These results are still being evaluated, however, it may be that penetration of the expected range-front fault is responsible for the abruptly lower gradient below about 655m (2150 feet).

# TEMPERATURE (°F)




Figure 19  
EQUILIBRIUM PROFILE  
GRACE GEOTHERMAL  
HOLE NO. 45-14

2/03/83

SOUTHWEST DRILLING & EXPLORATION  
ST. GEORGE, UTAH

TD = 3640  
FEET  
BHT = 247.40  
DEG F

(from Southwest Drilling and Exploration, 1983a)

## References

- Blair, G.N., 1980, Geochemical Soil Survey, Baltazor Thermal Area, Nevada: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.
- EPPC, 1979, 27 shallow thermal gradient holes-temp. and lithology: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.
- EPPC, 1980, Deep thermal gradient study of 3 holes to 1500 ft; temp. logs, drilling and completion histories, location map: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.
- Edquist, R.K., 1981, Geophysical investigations of the Baltazor KGRA and the Painted Hills Thermal Area, Humboldt County, Nevada: Univ. of Utah DOE/DGE Rpt. DOE/ID/12079-29, ESL-54.
- Gardner, M.C., and Koenig, J.B., 1978, Photogeologic interpretation of the Baltazor-McGee (Painted Hills) geothermal prospects, Humboldt County, Nevada: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.
- Hulen, J., 1979, Geology and alteration of the Baltazor Hot Springs and Painted Hills thermal areas, Humboldt County, Nevada: Univ. Utah Rsch. Inst., Earth Science Lab., report no. 27.
- Klein, C.W. and Koenig, J.B., 1977, Geothermal interpretation of groundwaters, Continental Lake region, Humboldt County, Nevada: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.
- Mining Geophysical Surveys, Inc., 1980, Resistivity and self-potential survey, Baltazor-McGee geothermal prospects, Humboldt County, Nevada: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.
- Peterson, D.L., and Hoover, D.B., 1977, Principal facts for a gravity survey of Baltazor Known Geothermal Resource Area, Nevada: U.S. Geological Survey, OFR, 77-67C, 4 p.



Plouff, D., Robbins, S.L., and Holden, K.D., 1976, Principal facts for gravity observations in the Charles Sheldon Antelope Range, Nevada - Oregon: U.S. Geological Survey, OFR, 76-601, 22 p.

Sass, J.H., Lachenbruch, A.H., Munroe, R.J., Greer, G.W., and Moses, T.H., 1971, Heat flow in the western United States: Journ. Geophys. Research, v. 76, no. 26, p. 6376-6413.

Scintrex Mineral Surveys, Inc., 1972, Aeromagnetic map of the Baltazor-McGee geothermal prospects: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.

Senturion Sciences, Inc., 1977, Northwestern Nevada micro-earthquake survey report: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.

Southwest Drilling and Exploration, 1983a, Final report: Grace Geothermal Corp. Baltazor Hot Springs, Nevada Hole No. 45-14: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.

Southwest Drilling and Exploration, 1983b, Temperature survey dated February 3, 1983, Baltazor 45-14: Univ. Utah Rsch. Inst., Earth Science Lab., OFR.

APPENDIX A. DATA ON OPEN FILE AT UURI

Open-file Materials

Open-file materials generated under Department of Energy's Industry Coupled Program, and from Earth Science Laboratory research, are available in reproduction at duplicating and handling cost from:

Publications  
Earth Science Laboratory  
420 Chipeta Way, Suite 120  
Salt Lake City, Utah 84108

<u>OFR #</u>	
NV/BAL/EPP-1	Geothermex report: "Geothermal Interpretation of Groundwaters, Continental Lake Region, Humboldt Co., Nevada" (Dec 1977) \$2.50
NV/BAL/EPP-2	Geothermex report: "Photogeologic Interpretation of the Baltazor-McGee Geothermal Prospect, Humboldt Co., Nevada". \$1.30
NV/BAL/EPP-3	Senturion Science Inc. report: "NW Nevada Microearthquake Survey Report for Earth Power Production Corp."; two, 6-station, 9-km diameter seismometer arrays. \$6.05
NV/BAL/EPP-4	27 shallow thermal gradient holes: temperatures, lithology, temperature gradient map. \$2.75
NV/BAL/EPP-5	Aeromagnetic map, Vya sheet: 1,015 sq mi; scale 1:62,500, flown at 9000 ft by Scintrex Mineral Surveys in 1972. \$1.35
NV/BAL/EPP-6	Gravity map from USGS Open-File 76-601 & 77-67C @ 400 sq mi. \$1.35
NV/BAL/EPP-7	Earth Power Production Co: Geochemical map, geologic cross section, sulfate map, micro-earthquake survey map. \$4.35
NV/BAL/EPP-8	Three deep thermal gradient holes (to 1500 ft): temperature logs, drilling & completion histories, location map. \$3.00
NV/BAL/EPP-9	Dipole-dipole resistivity survey, 10 line miles at a=1500 ft; self-potential survey, 20 line miles at 200 meter stations; by Mining Geophysical Surveys Inc. (Mar 1980). \$3.85

NV/BAL/EPP-10      Geochemical soil survey (Hg, As) for 173  
 samples at 1000 ft station spacing covering  
 @ 5 sq mi.      \$1.25

\*                      Driller's logs, 0-2529 feet, Baltazor 45-14.    \$\*

\*                      Geophysical logs, Gearheart-Owens, 39-418 feet,  
 Baltazor 45-14.    \$\*

\*                      Temperature surveys dated 10/31/82 and 11/25/82,  
 Baltazor 45-14.      \$\*

\*                      Drilling history, drilling data log and daily  
 mud logs, 0-2529 feet, Baltazor 45-14.    \$\*

\*                      Final report, Southwest Exploration, 0-2529 feet,  
 Baltazor 45-14.      \$\*

\*                      Geophysical logs, Gearheart-Owens, 402-3609  
 feet, Baltazor 45-14.    \$\*

\*                      Exlog Smith mud logs, 2540-3703 feet, Balt-  
 azor 45-14.          \$\*

\*                      Calvert Western drillers' logs, 0-3703 feet,  
 Baltazor 45-14.      \$\*

\*                      Temperature survey dated 2/03/83, 0-3640  
 feet, Baltazor 45-14.    \$\*

\* To be determined by ESL/UURI