



occasional cobbles and boulders throughout

EXPLANATION

- █ FUGRO DRIVE SAMPLE
- ▤ BULK SAMPLE
- █ PITCHER TUBE SAMPLE
- ▤ STANDARD PENETRATION TEST SAMPLE
- ▨ CORE SAMPLE
- N - STANDARD PENETRATION RESISTANCE
- ▲ - DRY UNIT WEIGHT (ASTM: D-2937-71)
- - MOISTURE CONTENT (ASTM: D-2216-71)
- NR - NO RECOVERY
- * - N VALUE > 100
- † - TEST LOCATION APPROXIMATELY 5 FEET FROM BORING

BORING DETAILS

- ELEVATION : 2540' (774m)
- SURFICIAL GEOLOGIC UNIT : A5y/A5i
- DATE DRILLED : 18 October 1980
- DRILLING METHOD : Rotary Wash
- HOLE DIAMETER : 4 7/8" (124mm)
- WATER LEVEL : Not Encountered

FUGRO NATIONAL, INC.

LOG OF BORING CE-B-5
OPERATIONAL BASE SITE
COYOTE SPRING VALLEY, NEVADA

MX SITING INVESTIGATION
DEPARTMENT OF THE AIR FORCE BMO

FIGURE II-2-5
AFV-06