CENTURY GEOPHYSICAL CORPORATION

Tulsa, Oklahoma

OPERATOR	F. JONES
DATE	08-28-80
UNIT NO.	7740
FIELD OFFICE	CARSON CITY

COMPANY	FUGRO NATIONAL
BOREHOLE	HC-S-T-2
AREA	HOT CREEK VALLEY
ELEVATION	
COUNTY	NYE
STATE	NEVADA
SECTION	27ac
TOWNSHIP	6N
RANGE	50E

PRELIMINARY

HOLE DATA

TOTAL DEPTH — DRILLER	510	BIT SIZE	12.3"
TOTAL DEPTH — LOGGER	510	CASING — TYPE & SIZE	NONE
TOTAL FOOTAGE LOGGED	510	CASING DEPTH	NONE
LOGGING SPEED	60/MIN	BOREHOLE FLUID	MUD
REFERENCE LEVEL	G.L	FLUID RESISTIVITY	5.1 @81°F
PROBE NO.	9055A-238	SOFTWARE LEVEL	V3L10

REMARKS:

EQUIPMENT DATA

	PROBE MODEL	9010	9030	9050/55	9060
	PROBE DIAMETER	1.87"	2.0"	1.87"	1.4"
NATURAL GAMMA	DETECTOR TYPE	NaI	NaI	NaI	NaI
	DETECTOR SIZE	.875" x 1.25"	1.25" x 4.5"	.875" x 4.0"	.5" x 3.0"
	STD. K FACTOR	1.59 x 10⁻⁵	—	.550 x 10⁻⁵	1.62 x 10⁻⁵
	STD. DEADTIME	1 μsec	—	1.18 μsec	1 μsec
	CALIB. MODEL LOC.		—	G.J.	
	CALIB DATE		—	6-9-80	
	K FACTOR		—	5.6×10^{-6}	
	DEADTIME		—	1.1×10^{-6}	
	TEST READING		—	—	
	WATER FACTOR		—		
	CASING FACTOR		—	—	
DENSITY	DETECTOR TYPE	—	NaI	—	NaI
	DETECTOR SIZE	—	.5" x 1.5"	—	.5" x 3.0"
	SOURCE TYPE	—	Cs137	—	Cs137
	SOURCE NO.	—		—	
	SOURCE STRENGTH	—		—	
	SOURCE SPACING	—		—	
NEUTRON	DETECTOR TYPE	—	—	He3	—
	DETECTOR SIZE	—	—	1.0" x 6.0"	—
	SOURCE TYPE	—	—	AmBe	—
	SOURCE NO.	—	—	—	—
	SOURCE STRENGTH	—	—	—	—
	SOURCE SPACING	—	—	—	—
	SNGL. PT RESISTANCE	1.4"D x 2.5"L	—	1.4"D x 2.5"L	1.1"D x 2.5"L
	RESISTIVITY	—	6" FOCUSED	—	—
	SELF POTENTIAL	YES	—	YES	YES
	TEMPERATURE	—	—	YES	—
	DEVIATION	—	—	YES	—
	CALIPER	—	YES	—	—

CT-112 REV. 11-78

CENTURY GEOPHYSICAL CORP. PART NO. 786-0022

PRINTED IN U.S.A.

COMPU-LOG V3L9 PLOT 08-28-80

HC-S-T-2
FUGRO NATIONAL
HOT CREEK VALLEY
HOLE DIAMETER : 12.3

CAL STD CPS = 0000 CAL RUN CPS = 0000
PROBE # 9055A -238 PROBE CAL BIAS = +00000
TRUCK # 7740 DATA: V3L10
APPL.#3 D
JONES. F.

VERTICAL DEVIATION

COMPULOG V3L1 DEVIATION

HOLE ID: HC-S-T-2

SCALE: 1 FT/IN
MAG DECL: 15.0
TRUE DEPTH: 510. FT
AZIMUTH: 64.
DISTANCE: 1.0 FT

+ = 25 FOOT INCR
△ = TOP OF ZONE
◇ = BOTTOM OF ZONE
TRUE NORTH ↑