GL04920_2

Welex
2"=100'

DUAL INDUCTION GUARD LOG

MT-1 2" LINEAR CORRELATION LOG

COMPANY AMAX EXPLORATION INCORPORATED
WELL MC COY 14-7
FIELD DIXIE VALLEY
County CHURCHILL State NEVADA

COMPANY AMAX EXPLORATION INCORPORATED
WELL MC COY 14-7
FIELD [redacted] McCoy
COUNTY CHURCHILL STATE NEVADA
Location N/A SW-NW
27-001-90031
Sec. 7 Twp. 23 N. Rge. 40 E.

Other Services:
CAVL
NUCENS.
3

Permanent Datum G.L. Elev. 4560
Log Measured From G.L. Ft. Above Perm. Datum
Drilling Measured From G.L.

Elev.: K.B. N/A
D.F. N/A
G.L. 4560

Date	05-22-80			
Run No.	ONE			
Depth—Driller	2010			
Depth—Welex	1982			
Btm. Log Intvl.	1979			
Top Log Intvl.	505			
Casing—Driller	8 5/8 @ 505	@	@	@
Casing—Welex	505			
Bit Size	6 1/2			
Type Fluid in Hole	GEL-WATER			
Dens. / Visc.	N/A / N/A			
pH / Fluid Loss	N/A / N/A ml	ml	ml	ml
Source of Sample	PIT			
R_m @ Meas. Temp.	N/A @ N/A °F	@ °F	@ °F	@ °F
R_{mf} @ Meas. Temp.	N/A @ N/A °F	@ °F	@ °F	@ °F
R_{mc} @ Meas. Temp.	N/A @ N/A °F	@ °F	@ °F	@ °F
Source R_{mf} R_{mc}	N/A N/A			
R_m @ BHT	N/A @ N/A °F	@ °F	@ °F	@ °F
Time Since Circ.	LAST CIRC.			
Max. Rec. Temp.	175 °F @ 2HT	°F @	°F @	°F @
Equip. / Location	8586 / MIDLND			
Recorded By	TAYLOR/ADOVE			
Witnessed By	GROSS			

Reproduced By
Petroleum Information
CORPORATION
MIDLAND, TEXAS 79701

REFERENCE K 9282N

3 COMPLETION RECORD

SPUD DATE

COMP DATE

DST RECORD

API NO.

CASING RECORD

PERFORATING RECORD

ACID, FRAC SHOT

I P

GOR GR

T P C P

REMARKS:

REPRODUCTION FOR RESALE PROHIBITED

Service Ticket No. 05582 's Remarks

Change in Mud Type or Additional Samples

Date / Sample No.		
Depth—Driller		
Type Fluid in Hole		
Dens. / Visc.		
pH / Fluid Loss	ml	ml
Source of Sample		
R_m @ Meas. Temp.	@ °F	@ °F
R_{mf} @ Meas. Temp.	@ °F	@ °F
R_{mc} @ Meas. Temp.	@ °F	@ °F
Source R_{mf} R_{mc}		
R_m @ BHT	@ °F	@ °F
R_{mf} @ BHT	@ °F	@ °F
R_{mc} @ BHT	@ °F	@ °F

SCALE CHANGES

Type Log	Depth	Scale Up Hole	Scale Down Hole

EQUIPMENT DATA

Run No.	Tool Type and No.	Pad Type	Tool Position	Other
ONE	DIC 5182A		STAN 1 1/2	

2"=100'

POTENTIAL MILLIVOLTS

RESISTIVITY OHMS M²/M

CONDUCTIVITY M MHOS/M

Rmf at °F.

0	16" NORMAL	100	500	DEEP INDUCTION	0
0	0.S.	1000	1000	0.S.	500
0	AMPLIFIED NORMAL	20			
0	DEEP INDUCTION	100			
0	0.S.	1000			

ONE MINUTE INTERVAL MARKER

16" NORMAL

DEEP INDUCTION

500 600 700 800 900 1000 1100 1200 1300 1400 1500 1600 1700 1800 1900

ONE MINUTE INTERVAL MARKER

16" NORMAL

DEEP INDUCTION

0	DEEP INDUCTION	100			
0	0.S.	1000			
0	SHALLOW GUARD	100	500	DEEP INDUCTION	0
0	0.S.	1000	1000	0.S.	500
0	AMPLIFIED GUARD	20			

Rmf at °F.

POTENTIAL MILLIVOLTS

RESISTIVITY OHMS M²/M

CONDUCTIVITY M MHOS/M

AMAX EXPLORATION INCORPORATED
MC COY 14-7
DIXIE VALLEY
CHURCHILL COUNTY, NEVADA

T.D. LOGGED 1979
T.D. DRILLER 2010
T.D. WELEX 1982

REPEAT SECTION

1800 1900