

AMAX

John Deymonaz

<u>Hole Number</u>	<u>Depth Interval</u>	<u>Bulk Conductivity</u>
620-SA		6.35
620-SB		5.31
620-38	150-200 feet	5.07
620-38	270-320	4.93
620-38A	270-320	4.94
620-39	250-320	4.71
620-43	180-288	4.63
620-46		3.99
620-47	10-180	3.24
620-47	180-300	5.16
620-48	250-320	4.95
620-50	180-240	11.34
620-50	240-320	11.23
620-50A	240-320	9.38
620-52	220-280	6.27
620-52	280-300	5.68
620-52A	220-280	6.10
620-60	80-140	5.44
620-60	230-280	3.78

AMAX
Livermore

<u>Hole Number</u>	<u>Depth Interval</u>	<u>Bulk Conductivity</u>
620-58K	70 - 100 feet	7.63
620-58K	210 - 230	6.03
620-58K	270 - 300	7.12
620-44K	180 - 230	4.56
620-44K	230 - 270	3.76
620-62K	200 - 220	3.75
620-54	160 - 190	4.55
620-59K	80 - 120	4.78
620-59K	160 - 200	4.65
620-59K	260 - 300	5.38
620-59A K	80 - 120	4.30
620-36K	230 - 270	4.39
620-46K	210 - 260	3.68
620-54	270 - 300	5.50

AMAX

Livermore, California

<u>Site</u>	<u>Depth</u>	<u>Bulk Conductivity</u>
620-31K	160 - 320 ft.	6.66
620-33K	200 - 220	4.84
620-33A	200 - 220	4.26
620-34K	180 - 320	6.93
620-40K	260 - 320	10.73
620-40A	260 - 320	10.18
620-41K	260 - 320	9.97
620-42K	260 - 320	7.84
620-43K	250 - 290	5.33
620-51K	50 - 160	5.60
620-63K	210 - 240	7.31

<u>Hole #</u>	<u>Depth (feet)</u>	<u>Bulk Conductivity millicalories/cm-sec-°C</u>
620-11	30'	7.58
620-10	1910'	6.65
620-9	1480'	9.10
620-10	970'	5.74
620-9	1910'	8.66
620-9	910'	9.37
620-11	1200'	8.44
620-11	1090'	9.12
620-9	520'	6.39
620-10	1400'	6.15
620-11	1930'	7.11
620-10	100'	2.69