

AMAX EXPLORATION, INC.  
TEMPERATURE/DEPTH LOG

(FL-23)

AT Well No. 1191-12

Property-Project Fish Lake Depth Logged 42m  
 Map Davis Mtn Scale \_\_\_\_\_ Date: Drilled 4-20-81 Logged 8-3-81  
 State Nv County Esmeralda of \_\_\_\_\_ of NE of SW of Sec 2 T 15 R 35E  
 Instrument Enviro-labs Operator JED Elevation 5440 (ft/m)  
 Comments 2" H2O Filled PVC set in open 6" casing

RT JUSTIFY

Date Logged

| Proj No              | Well No                       | DA | MO | YR | *    |
|----------------------|-------------------------------|----|----|----|------|
| 1 2 3 4 5 6 7 8 9 10 | 11 12 13 14 15 16 17 18 19 20 |    |    |    |      |
| 1171                 | 1203                          | 08 | 08 | 31 | C.M. |

\*19-Write F if Fahrenheit, 20-Write F if Feet

Site Description

| Operator                      | Editor                        | DA                            | MO                            | YR                      |
|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------|
| 21 22 23 24 25 26 27 28 29 30 | 31 32 33 34 35 36 37 38 39 40 | 41 42 43 44 45 46 47 48 49 50 | 51 52 53 54 55 56 57 58 59 60 | 61 62 63 64 65 66 67 68 |
| 10.7 KM SW GAP SPG A          |                               |                               | JED                           | OP                      |
|                               |                               |                               | 20                            | 04                      |

(Approx. location, water well?, oil test?, etc.)

Map Location \*\*

Scale Unit CM Map Size (7.5, 15, 60) 15.0 N Lat Degree 37.45.0 W Long Degree 118.15.0

Measure from SW corner of map; except AMS sheets measure from bottom center degree mark (W,-)(E,+)

Use decimals

Northring 23.0 Easting 26.95 Elev 5440

Use decimals

Write M if meters

Segment 1 = Depths

| Start                         | End                           | Conductivity K                | ΔK   | Best cond. (-K) |
|-------------------------------|-------------------------------|-------------------------------|------|-----------------|
| 21 22 23 24 25 26 27 28 29 30 | 31 32 33 34 35 36 37 38 39 40 | 41 42 43 44 45 46 47 48 49 50 |      |                 |
|                               | 10.0                          | 40.0                          | -3.0 | -0.5            |

Segment 2 Start →

|                               |                               |                               |  |  |
|-------------------------------|-------------------------------|-------------------------------|--|--|
| 51 52 53 54 55 56 57 58 59 60 | 61 62 63 64 65 66 67 68 69 70 | 71 72 73 74 75 76 77 78 79 80 |  |  |
|                               | 999                           |                               |  |  |

Segment 3 Start →

Segment 4 Start →

Segment 5 Start →

Segment 6 Start →

Segment 7 Start →

Segment 8 Start →

Segment 9 Start →

Segment 10 Start →

After final segment Start = 999

HOLE 1191-12

Lithic Tuffs of pumice & rhyolite frags - non welded - Dry to TD



