RESOURCES AGENCY OF CALIFORNIA DEPARTMENT OF CONSERVATION

DIVISION OF OIL, GAS, AND GEOTHERMAL RESOURCES

API Well No. 097-90851

WELL SUMMARY REPORT — GEOTHERMAL

Operator Geysers Po			Well Sulfur Bank 34													
Field Geysers						County Sonoma					Sec. 12	T.	N	R. 9W	B.&M. M.D.	
Location (Give surface location from property or section corner, street 667.1' North and 2053.9' East of the SW Corner of Section 12, T11											Elevation of ground above/below sea level 2096'					
								de: <u>-122.814730</u>								
Was the well directionally drilled? ☐ Yes ☐ No If yes, show coordinates at total depth. 1070' North and 169' of surface location (surveys attached)																
Commenced d 07/28/2012	pth T	True Vertical Depth		Plugged Depth		Depth measurements taken from top of: ☐ Derrick Floor ☐ Rotary Table ☒										
Completed drilling (date) 8258' 09/21/2012					8159'	Which is				· · · · · · · · · · · · · · · · · · ·						
Injection pending pipeline construction ceme				unk None. For more casing and ementing details please see attached asing tallies and cementing reports.					GEOLOGICAL MARKERS Refer to Litho-log				DEPTH			
						Formation and age at total d				pth Base of fresh wate			resh water			
	STATI	IC TEST					PROD	OUCTION TE	EST F	DATA						
DATE	(Shut-in well head)				otal mass flo		a		011011 1201 2711		Separator					
	(psig)		Sfc Pressure (psi)	Orifice (Inches)			Enthalpy (Btu/lb)	Temperature (°F)	Sf	c Pressure (psi)		Temperature (°F)		n Rate s/hr)	Water Rate (lbs/hr)	
09/13/12	Rig Test / Wet Test															
Cinc of Cooling (ADI)						NTING RECORD Grade and Type						f C l		Tam/a)	at Camant	
Size of Casing (API) (inches)		Top of Casing (feet)	(feet)	oe '	Weight of Casing (lbs/ft)		of Casing	Drilled			ber of Sacks or Feet of Cement			Top(s) of Cement in Annulus (feet)		
20"		surface	537'	94	94#		5 C	26"		480 sx				surface		
13-3/8" X 13-5/8"		surface	2434'		68# X 88.2#		0 C	17-1/2"		1050 sx			surface			
8-5/8" X 7" slotted/blank liner		2239'	8195'	40	40#		3/80 H523 I JFE Bear	10-5/8"		N/A			N/A			
7" tieback		surface	2278'	29	29#		3/80 JFE ar	13-5/8" casing		N/A			N/A			
PERFORATED CASING LINER (Size, top, bottom, perforated intervals, size and spacing of perforations, and method.) 8-5/8" X 7" slotted liner 2-1/2" X 1/4" 6 rows, 12 spf, blank 8' from box and 4' from pin																
Logs/surveys run? ☐ Yes ☒ No If yes, list type(s) and depth(s).																
			n 3, of the <i>Pub</i> e thereon, so fa							is a compl	ete and	correct	recor	rd of the	e present	
Name Paul Graham									Title Agent							
Address 10350 Socrates Mine Road										City/State Middletown, CA					ip Code 5461	
Telephone 707 431-6094						Signature						Date				
E-Mail grahampaul@calpine.com					Fax 707-431-6148											

OGG100 (4/08)