

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION
DIVISION OF OIL, GAS, AND GEOTHERMAL RESOURCES
WELL SUMMARY REPORT — GEOTHERMAL

API Well No. **097-90832**

Operator Geysers Power Company, LLC				Well WHS-71					
Field Northwest Geysers				County Sonoma		Sec. 3	T. 11N	R. 8W	B.&M. M.D.
Location (Give surface location from property or section corner, street center line.) 1798.3' North & 2950.8' East of the SW corner of Section 3							Elevation of ground above/below sea level 2,573'		
Latitude/Longitude (if known) Latitude: _____ Longitude: _____									
Was the well directionally drilled? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No If yes, show coordinates at total depth. 1894' North & 351' West of surface location (surveys attached)									
Commenced drilling (date) 01/29/2010		Total depth	True Vertical Depth	Plugged Depth	Depth measurements taken from top of: <input type="checkbox"/> Derrick Floor <input type="checkbox"/> Rotary Table <input checked="" type="checkbox"/> Kelly Bushing				
Completed drilling (date) 10/02/2010		9,976'	9714'	N/A	Which is 28' feet above ground				
Commenced production/injection (date) Production pending pipeline construction		Junk N/A			GEOLOGICAL MARKERS Refer to Litho-log		DEPTH		
Name of production/injection zone(s) Franciscan					Formation and age at total depth Jurassic		Base of fresh water		

DATE	STATIC TEST (Shut-in well head)	PRODUCTION TEST DATA									
		Total mass flow data					Separator data				
		Pressure (psig)	Sfc Pressure (psi)	Orifice (Inches)	Rate (lbs/hr)	Enthalpy (Btu/lb)	Temperature (°F)	Sfc Pressure (psi)	Temperature (°F)	Steam Rate (lbs/hr)	Water Rate (lbs/hr)

CASING AND CEMENTING RECORD (Present Hole)							
Size of Casing (API) (inches)	Top of Casing (feet)	Depth of Shoe (feet)	Weight of Casing (lbs/ft)	Grade and Type of Casing	Size of Hole Drilled (inches)	Number of Sacks or Cubic Feet of Cement	Top(s) of Cement in Annulus (feet)
20"	surface	614'	94#	J-55 BTC	26"	570 sx	surface
13-3/8"	surface	4,201'	68# / 88.2#	L80 / K55 BTC	17-1/2"	2815 sx	surface
7"X8-5/8" liner							
	5,888' / surface	11,753' / 5,903'	32#, 29# & 26#	L-80 H-521 & BTC	8-1/2"	N/A	N/A

PERFORATED CASING LINER (Size, top, bottom, perforated intervals, size and spacing of perforations, and method.)
7"X8-5/8" slotted/blank liner 2-1/2" X 1/4" 6 rows, 12 spf and 2-1/2"X1/4" 10 rows, 20 spf, blank 8' from box and 4' from pin

Logs/surveys run? Yes No If yes, list type(s) and depth(s).

In compliance with Sec. 3215, Division 3, of the *Public Resources Code*, the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Name Paul Graham		Title Agent	
Address 10350 Socrates Mine Road		City/State Middletown, CA	Zip Code 95461
Telephone 707-431-6094	Signature <i>Paul Graham</i>		Date <i>09/16/2010</i>
E-Mail grahampaul@calpine.com	Fax 707-431-6148		