

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION
DIVISION OF OIL, GAS, AND GEOTHERMAL RESOURCES
WELL SUMMARY REPORT — GEOTHERMAL

API Well No. **097-90630**

Operator CPN Wild Horse, LLC		Well Prati 32				
Field Northwest Geysers		County Sonoma	Sec. 35	T. 12N	R. 9W	B.&M. MD
Location (Give surface location from property or section corner, street center line.) 3898' South & 1036' East of the NW corner of Section 35					Elevation of ground above/below sea level 2,116'	
Latitude/Longitude (if known)		Latitude: 38.839038		Longitude: -122.836302		
Was the well directionally drilled? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No If yes, show coordinates at total depth. 202' North and 1594' West of surface location						

Commenced drilling (date) 04/30/2011	Total depth	True Vertical Depth	Plugged Depth	Depth measurements taken from top of: <input type="checkbox"/> Derrick Floor <input type="checkbox"/> Rotary Table <input checked="" type="checkbox"/> Kelly Bushing
Completed drilling (date) 05/22/2011	11,143'	10,913'		Which is 31 feet above ground
Commenced production/injection (date) Injection pending pipeline hookup	Junk N/A			GEOLOGICAL MARKERS
Name of production/injection zone(s) Fransiscan				DEPTH
				Formation and age at total depth Jurassic
				Base of fresh water

DATE	STATIC TEST (Shut-in well head)	PRODUCTION TEST DATA									
		Total mass flow data					Separator data				
		Pressure (psig)	Sfc Pressure (psi)	Orifice (Inches)	Rate (lbs/hr)	Enthalpy (Btu/lb)	Temperature (°F)	Sfc Pressure (psi)	Temperature (°F)	Steam Rate (lbs/hr)	Water Rate (lbs/hr)

CASING AND CEMENTING RECORD (Present Hole)							
Size of Casing (API) (inches)	Top of Casing (feet)	Depth of Shoe (feet)	Weight of Casing (lbs/ft)	Grade and Type of Casing	Size of Hole Drilled (inches)	Number of Sacks or Cubic Feet of Cement	Top(s) of Cement in Annulus (feet)
22", 16" & 13-3/8 deleted for space							
11-3/4" liner	2805'	6113'	54 & 60#	K55, N80 & S95 BTC	14-3/4" hole	N/A	N/A
8-5/8" scab liner	surface	3545'	40#	L80 H-521	13-3/8 casing	1120 sx	surface
5-1/2" hangdown string	surface	8390'	17#	L-80 Hunting SLSF	8-5/8 casing	N/A	N/A

PERFORATED CASING LINER (Size, top, bottom, perforated intervals, size and spacing of perforations, and method.)
7" 29# L80 H-521 slotted liner from 10,004 - 11115', 8-5/8" 40# L80 H521 slotted liner from 6801 - 10,004', 8-5/8" 40# L80 H521 blank liner from 5904 - 6801. (7") slots 2-1/2" X 1/4" 6 rows, 12 spf, blank 8' from box and 4' from pin (8-5/8") slots 2" X 1/4" 10 rows, 20 spf, blank 8' from box and 4' from pin.

Logs/surveys run? Yes No If yes, list type(s) and depth(s).

In compliance with Sec. 3215, Division 3, of the *Public Resources Code*, the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Name Paul Graham		Title Agent	
Address 10350 Socrates Mine Road		City/State Middletown, CA	Zip Code 95461
Telephone 707-431-6094	Signature		Date 06/15/2011
E-Mail grahampaul@calpine.com	Fax 707-431-6148		